



ISCOR VANDERBIJLPARK STEEL
ENVIRONMENTAL MASTER PLAN

SPECIALIST REPORT

GEOTECHNICAL

BY
VAN RENSSSEN & FORTUIN
CONSULTING ENGINEERS

SERIES IV
DOCUMENT IVS/SR/042
DECEMBER 2002



ISCOR VANDERBIJLPARK STEEL

ENVIRONMENTAL MASTER PLAN

SPECIALIST REPORT

GEOTECHNICAL

BY

VAN RENSSSEN & FORTUIN

CONSULTING ENGINEERS

SERIES IV

DOCUMENT IVS/SR/042

DECEMBER 2002

Draft for discussion
CONFIDENTIAL
Research for IVS



OCKIE FOURIE
TOXIKOLOGE TOXICOLOGISTS
(ELAB) BPV (PTY) LTD
TEL: 012 348-9732/7



FRANCOIS MARAIS & ASSOCIATES
Consulting Engineers • Randspesende Ingenieurs
Tel: (012) 998-5886



ENPRO
Omgewingsakeunde / Environmental Advisors
Tel: (012) 471153



VAN RENSSSEN & FORTUIN
Consulting Engineers / Randspesende Ingenieurs
Tel: (012) 362 0991



Jasper Müller Associates
Consulting Scientists in Geochimistry
Tel: (013) 665 1788



Moolmans
ATTORNEYS
Tel: (011) 483-3704



KEN SMITH
ENVIRONMENTALISTS
TEL: (017) 82 61434 / 27



RICHARD PAXTON
ASSOCIATES LIMITED
Tel: 0944-1543 250939



ISCOR VANDERBIJLPARK STEEL



MASTER PLAN SPECIALIST REPORT: GEOTECHNICAL

DECEMBER 2002

Prepared by:
SOILKRAFT cc
For:
VAN RENSSSEN & FORTUIN (Pty) Ltd
On behalf of:
OCKIE FOURIE TOXOCOLOGISTS (Pty) Ltd



ISCOR FLAT STEEL PRODUCTS VANDERBIJL PARK : PROPOSED MASTER PLAN FOR WASTE MANAGEMENT - FINAL GEOTECHNICAL REPORT

INDEX

1	APPOINTMENT	1
2	EXTENT OF REPORT	1
3	METHOD OF INVESTIGATION	2
4	REGIONAL GEOLOGY	3
5	DISCUSSION	4
6	CONCLUSIONS AND RECOMMENDATIONS	13
7	ADDENDUM A : TEST PIT PROFILES	15
8	ADDENDUM B : AUGER HOLE PROFILES	82
9	ADDENDUM C : RESULTS OF DSH PROBING	94
10	ADDENDUM D : RESULTS OF SOIL TESTING	151

Soilkraft cc

Reg no CK 96/08031/23

PO Box 73478
Lynnwood Ridge
0040
Tel : 012-9912555
Cell : 0825702767
Email: soilkraf@iafrica.com

ISCOR FLAT STEEL PRODUCTS VANDERBIJL PARK : PROPOSEO MASTER PLAN FOR WASTE MANAGEMENT – FINAL GEOTECHNICAL REPORT

1 APPOINTMENT

Soilkraft cc was appointed by Mr C van Renssen of Van Renssen and Fortuin Consulting Engineers to assist them with the assessment of the geotechnical conditions at various places in the existing site of the Iscor works at Vanderbijl Park. The report serves the purpose to allow an input to the development of a master plan for pollution control at the existing premises and deals specifically with shallow geotechnical conditions and soil characteristics.

2 EXTENT OF THE REPORT

This document is issued as a report to provide a geotechnical input to the proceedings of the total investigation. The areas covered are :

- The existing waste site.
- The site for the proposed new dams.
- The proposed new waste site.
- The existing dams.
- The north western and south eastern perimeter areas.
- The Cyferpan and farmlands areas.

The emphasis of the investigation varied for various parts of the site, but in general it was aimed at :

- Determining the susceptibility of the soil profile to pollution.
- Determining the presence of pollutants in the soil profile.
- Determining the suitability of in situ soil materials for the construction of various types of earthworks.

3 METHOD OF INVESTIGATION

The field work for the investigation was undertaken in the period 11 March 2002 to 25 March 2002. It consisted of the following :

3.1 Test Pitting

Sixty six test pits were excavated with a Caterpillar 416 TLB on hire from Vuma Construction in the various areas as required and where the sites were accessible to the equipment. The test pits were profiled according to the standard profiling parameters as proposed by the Geotechnical Division of SAECI and SAIEG. For easy reference these parameters are summarized in the attached Table 1 : Soil Descriptive Terms The test pit profiles are contained in Addendum A to this report.

3.2 Auger Drilling

Eleven auger holes were drilled to various depths across the site with a Williams 11 digger on hire from Soiltech. As this type of investigation is extremely expensive, the drilling was limited to the minimum and only areas considered important were investigated. The auger hole profiles are contained in Addendum B to this report.

3.3 DSH Probing

Fifty six sites were probed with a DSH probe provided by Mr Roelf Fourie. The aim of the probing was to act as an infill to the test pitting to obtain an indication of depth to bedrock. The results of the probing are contained in Addendum C to this report.

3.4 Soil Testing

The purpose of soil testing in general was :

- To obtain information regarding the suitability of the available materials for future construction of liners, earth embankments etc.
- To determine the permeability of certain materials and hence the susceptibility thereof to become polluted.

The results of the soil testing are contained in Addendum D to this report.

TABLE 1 : SOIL DESCRIPTIVE TERMS

CONSISTENCY : GRANULAR SOILS

CONSISTENCY : COHESIVE SOILS

SPT N	GRAVELS & SANDS Generally free draining soils		DRY DENSITY (kg/m ³)	SPT N	SILTS & CLAYS and combinations with SANDS. Generally slow draining soils		UCS (kPa)
<4	Very loose	Crumbles very easily when scraped with geological pick	<1450	<2	Very soft	Pick point easily pushed in 100mm Easily moulded by fingers	<50
4-10	Loose	Small resistance to penetration by sharp pick point	1450-1600	2-4	Soft	Pick point easily pushed in 30mm to 40mm Moulded by fingers with some pressure	50-125
10-30	Medium dense	Considerable resistance to penetration by sharp pick point	1600-1750	4-8	Firm	Pick point penetrates to 10mm Very difficult to mould with fingers	125-250
30-50	Dense	Very high resistance to penetration by sharp pick point, requires many blows by pick point for excavation.	1750-1925	8-15	Stiff	Slight indentation by pick point. Cannot be moulded by fingers. Penetrated by thumb nail.	250-500
>50	Very dense	High resistance to repeated blows of geological pick. Requires power tools for excavation.	>1925	15-30	Very stiff	Slight indentation by blow of pick point. Requires power tools for excavation.	500-1000

SOIL TYPE

SOIL TYPE	PARTICLE SIZE(mm)
Clay	<0,002
Silt	0,002-0,06
Sand	0,06-2,0
Gravel	2,0-60,0
Cobbles	60,0-200,0
Boulders	>200,0

MOISTURE CONITION

Dry	No water detectable
Slightly moist	Water just discernable
Moist	Water easily discernable
Very moist	Water can be squeezed out
Wet	Generally below water table

SOIL STRUCTURE

COLOUR		SOIL STRUCTURE	
Speckled	Very small patches of colour <2mm	Intact	No structure present
Mottled	Irregular patches of colour 2-6mm	Fissured	Presence of discontinuities, possibly cemented
Blotched	Large irregular patches 6-20mm	Stickensided	Very smooth, glossy, often striated discontinuity planes
Banded	Approximately parallel bands of varying colours	Shattered	Presence of open fissures. Soil break into gravel size blocks.
Streaked	Randomly orientated streaks of colour	Micro shattered	Small scale shattering, very closely spaced open fissures. Soil breaks into sand size crumbs.
Stained	Local colour variations : Associated with discontinuity surfaces	Residual structures	Residual bedding, laminations, foliations, etc.

ORIGIN

Transported	Alluvium, tillwash, talus, etc
Residual	Weathered from parent rock, eg residual granite
Pedocretes	Emcrete, siccrete, calcrete etc.

DEGREE OF CEMENTATION OF PEDOCRETES

TERM	DESCRIPTION	UCS (MPa)
Very weakly cemented	Some material can be crumbled between finger and thumb. Disintegrates under knife blade to a friable state	0,1-0,5
Weakly cemented	Cannot be crumbled between strong fingers. Some material can be crumbled by strong pressure between thumb and hard surface.	0,5-2,0
Cemented	Under light hammer blows disintegrate to a friable state. Material crumbles under firm blows of sharp pick point. Grains can be dislodged with some difficulty by a knife blade.	2,0-5,0
Strongly cemented	Firm blows of sharp pick point on hand-held specimen show 1-3mm indentations. Grains cannot be dislodged by knife blade.	5,0-10,0
Very strongly cemented	Hand-held specimen can be broken by single firm blow of hammer head. Similar appearance to concrete.	10,0-25

4 REGIONAL GEOLOGY

The area is covered by lithology belonging to the Transvaal Sequence, consisting of various shales, quartzitic sandstones and lavas. Most of the constituent beds have been subjected to folding and faulting and their thicknesses and delineation vary considerably. The area is situated on the

perimeter of the so-called Vredefort dome, and, on a large scale, a dome-like circular distribution of the stratigraphy can be identified. This phenomenon consists of a large scale synclinorium, which curves round the Vredefort Dome, and is known as the Vereeniging Dome.

The lithology of the area is intruded by sills of diabase associated with the Bushveld Complex. The width and distribution of these sills are highly variable and can be considered the dominating geological feature of the area.

Surface deposits of recent origin cover the entire site, although the thickness and composition there of vary considerably. In areas where shale is encountered at shallow depths, the soil cover tends to be argillaceous. Towards the south fine, light red, wind blown deposits of sand are present. However, the most important soil type is recently gravels of degradation present over large areas of the site. These gravels consist of cobbles and boulders of various materials embedded in ferruginous soils. Among the cobbles and boulders are chert, conglomerate and quartz. Some of the boulders attain a diameter of up to 1000mm.

The regional geology of the site is indicated on the attached Figure 1 : Regional Geology.

5 DISCUSSION

5.1 Existing Waste Site

The existing waste site was investigated by means of DSH probes 1 to 10. The probe curves are indicated on Figures C1 to C10 contained in Addendum C to this report.


The aim of the investigation was to determine whether there is a perched watertable present in the area. Probing is an inexpensive method of investigation, and it was considered to be a bonus if a watertable could be encountered and a piezometer installed. However, due to the composition of the waste materials, only limited penetration was possible and refusal generally occurred between 600mm and 5100mm deep without encountering any perched water.

5.2 Proposed New Dam Site

This area was investigated by means of :

- Eleven test pits as per Figures A1 to A11 contained in Addendum A to this report.
- DSH probes 25 to 38 as per Figures C25 to C38 contained in Addendum C to this report.

Draft for discussion
CONFIDENTIAL
Research for IVS



SOIL
KRAFT

REGIONAL GEOLOGY

FIGURE 1

5.2.1 Geology

Bedrock occurs typically as grey to brown Silverton shale. Bedrock was encountered at depths from 1500mm and deeper. Towards the north, in the areas of test pits 9, 10 and 11, intrusions of diabase cut through the shale and alternating occurrences there of occur in narrow bands, striking east to west.

5.2.2 Pedology

The soil profile consists typically of a surface horizon of transported sand, 200mm to 600mm thick, overlying residual silts and clays. Towards the south in the area where bedrock of shale occurs, the residual soils are generally of silty composition. Towards the north where a constant source of parent rock is not available, the material differs considerably from clays to silts. Ferruginization in the upper horizons of the clay and lower horizons of the transported material is common.

5.2.3 Material Properties

- *Potential Expansiveness* : The materials derived from the weathering of diabase must be regarded as moderately expansive with clay content of approximately 30%. Typically sandy clays and clayey sands have developed from the weathering of parent rock. The materials derived from the weathering of shale must be regarded as slightly expansive with a clay content of less than 10%. Typically sandy silts and clayey sands have developed from the weathering of parent rock.
- *Permeability* : Laboratory determined material permeabilities vary between $1,1 \times 10^{-5} \text{cms}^{-1}$ and $5,0 \times 10^{-6} \text{cms}^{-1}$. Calculated material permeabilities based on the material grading characteristics, vary between $8,12 \times 10^{-4} \text{cms}^{-1}$ and $6,11 \times 10^{-7} \text{cms}^{-1}$. Results of in situ seepage tests in three test pits indicated a rate of seepage varying between 0mm per hour to 1,9mm per hour.
- *Shear Characteristics* : The results of shear tests indicate the materials to be cohesionless, with a peak angle of internal friction varying between $30,7^\circ$ and $38,8^\circ$.

5.2.4 Material Excavability

Refusal of excavation occurred at depths between 2000mm and 3000mm. Refusal of probing occurred between 1500mm and 4500mm. A pattern of depth to refusal can not be established, as it is material source dependent. It was possible to excavate all soils with a TLB, but the clays in test pits 9 to 11 were very stiff and refusal of excavation took place in the clay horizon.

5.2.5 Perched Groundwater

No groundwater seepage or visible or odorous conditions of pollution were encountered.

5.2.6 Conditions of Pollution

Visible signs of pollution or odorous soils and waters were not encountered.

5.3 Proposed New Waste Site

This area was investigated by means of :

- Seven test pits as per Figures A12 to A18 contained in Addendum A to this report.
- One auger hole as per Figure B4 contained in Addendum B to this report.

5.3.1 Geology

Bedrock of shale was encountered in the auger hole only at a depth of 4800mm. Material properties of the residual soils encountered in most of the test pits indicate the area to be predominantly located on shale. However, the thick deposit of clay encountered in test pit 3 suggests the possible presence of a diabase intrusion.

5.3.2 Pedology

The pedology of the area is highly variable, consisting of a surface horizon of fill or silty sand overlying the pebblestone marker and residual clays and silts. The clays and silts are the products of weathering of either Silverton shale or diabase. Isolated areas of gravels of degradation were also encountered. Ferruginization of both the pebblestone marker and the residual soil is common. Perhaps the most important pedological feature of the area is the presence of the well developed and often ferruginized pebblestone marker.

5.3.3 Material Properties

- *Potential Expansiveness* : The materials derived from the weathering of shale must be regarded as slightly to moderately expansive with a clay content between 11% and 21%. Typically sandy silts to sandy clays have developed from the weathering of parent rock.
- *Permeability* : Laboratory determined material permeabilities of the residual soil vary between $6,7 \times 10^{-4} \text{cms}^{-1}$ and $1,1 \times 10^{-5} \text{cms}^{-1}$. Calculated material permeabilities based on the material grading characteristics, vary between $1,6 \times 10^{-4} \text{cms}^{-1}$ and $7,8 \times 10^{-7} \text{cms}^{-1}$. The presence of water in the test pits excluded the determination of in-situ permeability properties of the soil. The presence of water in the pebblestone marker indicates this horizon to be highly permeable.

5.3.4 Material Excavability

Refusal of excavation with the TLB usually took place between 1800mm and 3100mm. The auger hole refused at 5000mm on medium hard rock, shale. Conditions of excavation in both the shale and gravels of degradation can be regarded as hard. Soils can be regarded as soft excavation. Although it was difficult to penetrate the ferricrete with the TLB, it can still be regarded as removable by mechanical means. Conditions of excavation are greatly impeded by the presence of shallow perched water.

5.3.5 Perched Ground Water

Perched ground water was found to be present throughout the area. Several layers of perched water are present ; usually an extremely strong one within the highly permeable pebblestone marker and transported material, and a second just above bedrock. In test pit 6 (figure A17), the inflow of water was so strong that the test pit overflowed while excavation was in progress. The excavation and inspection of several pits had to be abandoned due to the influx of water and collapsing side walls.

5.3.6 Conditions of Pollution

No visible signs of pollution could be detected.

5.4 Existing Dam Site

This area was investigated by means of :

- Ten test pits as per Figures A19 to A28 contained in Addendum A to this report.
- Two auger holes as per Figures B5 and B6 contained in Addendum B to this report.
- DSH probes 11 to 24 as per Figures C11 to C24 contained in Addendum C to this report.

5.4.1 Geology

The eastern parts of the area are located on quartzite of the Daspoort Formation, but to the west a well developed diabase intrusion is present. The quartzite occurs as very hard rock, light red to light purple quartzitic sandstone. The diabase is deeply weathered and bedrock was not encountered at all. The structure of the residual diabase derived soil confirms the origin thereof.

5.4.2 Pedology

The pedology of the area is highly variable, consisting of a surface horizon of silty sand overlying Daspoort quartzites at very shallow depths in the east, to quaternary gravels and ferricrete overlying

diabase in the west. The residual diabase consists of yellowish, relic jointed sandy silts and is present to great depths.

The area immediately adjacent to the dams has been used as a borrow pit to obtain construction material for the damwalls. Especially the ferricrete and quaternary gravels have been removed for this purpose. The total effect is thus that over large parts the residual diabase has come in direct contact with seepage water from the dams.

5.4.3 Material Properties

- *Potential Expansiveness* : The materials derived from the weathering of diabase must be regarded as moderately expansive with a clay content of 29%. The pebblestone marker consists predominantly of gravels in a sand matrix and contains only 2% clay. It must therefore be regarded as non-expansive.
- *Permeability* : A laboratory determined material permeability on the residual diabase soil indicate the coefficient of permeability to be $3,7 \times 10^{-5} \text{cms}^{-1}$. The calculated material permeability of the residual diabase, based on the material grading characteristics, is $2,4 \times 10^{-7} \text{cms}^{-1}$; while the calculated permeability coefficient of the pebblestone marker is $3,04 \text{cms}^{-1}$. The presence of water in the test pits excluded the determination of in-situ permeability properties of the soil.

5.4.4 Material Excavability

Refusal of excavation with the TLB usually took place between 900mm and 2600mm : In the east on hard rock, quartzite and in the west on quaternary gravels or very dense ferricrete. . The auger holes refused at 12700mm and 18000mm respectively in the diabase. Refusal of probing took place between 1200mm (on ferruginized gravels) and 10500mm in the diabase. Conditions of excavation in the ferricrete, quartzitic sandstone and gravels of degradation can be regarded as hard. Soils can be regarded as soft excavation. Conditions of excavation are greatly impeded by the presence of shallow perched water.

5.4.5 Perched Groundwater

Perched ground water was found to be present throughout the area. Several layers of perched water are present ; usually an extremely strong one within the highly permeable pebblestone marker and transported material, and a second just above the dense ferricrete or on top of the less permeable residual diabase soil. bedrock. The excavation and inspection of several pits had to be abandoned due to the influx of water and collapsing side walls.

5.4.6 Conditions of Pollution

Tar is visibly present in the arenaceous surface soils, especially the pebblestone marker which acts as a preferential zone of seepage. Tar is also visible in the relic joints of the weathered diabase. The perched water and the weathered diabase encountered in the auger holes up to refusal smelt strongly of tar.

5.5 North Western Perimeter

This area was investigated by means of :

- Eleven test pits as per Figures A29 to A39 contained in Addendum A to this report.
- Four auger holes as per Figures B7 to B10 contained in Addendum B to this report.
- DSH probes 39 to 47 as per Figures C39 to C47 contained in Addendum C to this report.

5.5.1 Geology

This area is located on a well defined diabase intrusion and bedrock of diabase was encountered at depth in auger holes 7, 8 and 10. It is possible that more than one intrusion is present in the area, with the rock infills between the diabase consisting of shale.

5.5.2 Pedology

The pedology of the area consists mostly of clays and silts derived from the weathering of diabase and shale. Isolated occurrences of hardpan ferricrete are present. The materials can be considered as highly impermeable.

5.5.3 Material Excavability

Refusal of excavation with the TLB usually took place between 1100mm on ferricrete or excavation continued up to a depth of 3200mm in the clay. The auger holes refused between 3400mm and 6000mm. Refusal of probing took place between 300mm (on ferruginized gravels) and 10500mm in the clay. Excavation in the clays and silts can be regarded as soft. The ferricrete was much harder, but it will still be possible to remove it with heavy excavation equipment.

5.5.4 Perched Groundwater

Perched water was encountered locally and at depth only. Due to the impermeable soil profile, surface water is more common.

5.5.5 Conditions of Pollution

No visible signs of pollution were encountered.

5.6 South Eastern Perimeter

This area was investigated by means of :

- Three test pits as per Figures A40 ; A41 and A47 contained in Addendum A to this report.
- Two auger holes as per Figures B3 and B11 contained in Addendum B to this report.
- DSH probes 54 to 56 as per Figures C54 to C56 contained in Addendum C to this report.
- The investigation of the area was reduced due to the presence of several buried services in the area.

5.6.1 Geology

Bedrock in the area is covered by a horizon of very dense, quaternary gravels. It is presumed that these gravels overlie Timeball Hill shales.

5.6.2 Pedology

The pedology of the area consists of colluvial sand overlying a very dense horizon of ferruginized quaternary gravels.

5.6.3 Material Excavability

Refusal of excavation with the TLB usually took place between 1600mm and 2600mm in the gravels. The auger holes refused between 2700mm and 3000mm in the gravels. Refusal of probing took place between 1800mm and 2700mm in the gravels.

5.6.4 Perched Groundwater

Perched groundwater is present just above the ferruginized quaternary gravels and within the horizon of gravel itself. Although these gravels are impenetrable by the mechanical investigative procedures, they are not impervious, and seepage took place through and above them.

5.6.5 Pollution

No visible signs of pollution were encountered in the area.

5.7 Southern Perimeter

This area was investigated by means of :

- Five test pits as per Figures A42 to A46 contained in Addendum A to this report.
- Two auger holes as per Figures B1 to B2 contained in Addendum B to this report.
- DSH probes 48 to 51 as per Figures C48 to C51 contained in Addendum C to this report.
- The investigation of the area was reduced due to the presence of several buried services in the area.

5.7.1 Geology

An intrusion of diabase is encountered in the western part of the site, while hard rock, quartzitic sandstone is present in the east. The diabase was encountered at a depth of 5200mm in auger hole 1. The sandstone was encountered at a depth of 500mm in test pit 17 of the perimeter test pits.

5.7.2 Pedology

The pedology of the area consists of a transitional zone from the argillaceous clays and silts derived from diabase in the west, to arenaceous soils and gravels derived from Daspoort quartzite in the south. Residual clays were thus predominantly encountered in the west and thick surface deposits of sands in the south east. The clays can be regarded as moderately impermeable, but the sands as highly permeable.

5.7.3 Material Excavability

Refusal of excavation with the TLB usually took place between 800mm on quartzite and 2900mm in the clay. The auger holes refused between 1600mm and 5800mm. Refusal of probing took place between 1200mm on quartzitic sandstone and 3900mm in the sand.

5.7.4 Perched Groundwater

Perched water is quite common in the area, consisting of water usually present above bedrock.

5.7.5 Pollution

Recognizable pollution was encountered in test pit 17 (Figure A45) due to the strong smell of ammonia originating from the perched water.

5.8 Cyferpan and Farmlands Area

These areas were investigated by means of 19 test pits excavated with a TLB. The profiles are contained in Addendum A to this report. Extensive soil testing was undertaken to obtain indications of the suitability of the soil material for future utilization. The results of the soil testing are contained in Addendum D to this report.

5.8.1 Geology

The geology of the area consists of shale intruded by diabase sills and dykes. A deep soil profile is present on site and bedrock was not encountered in any of the test pits.

5.8.2 Pedology

The soil profile consists typically of a surface horizon of transported silty to clayey sand overlying residual clays and silts. The surface horizon of sand was between 450mm and 1500mm thick in the test pits. Residual clays and silts are derived from the weathering of diabase and shale. Ferruginization of the residual soil is common. The soil quality is dependent on the extent of ferruginization of the soil profile, rather than on the parent rock.

5.8.3 Material Properties

- *Potential Expansiveness* : All materials must be regarded as potentially moderately to highly expansive. The only limiting factor in this regard is the proportion of shale or ferricrete gravels contained in the soil matrix. In general the argillaceous materials have a clay content between 22% and 32% ; and the gravelly materials a clay content between 4% and 10%.
- *Permeability* : Laboratory determined material permeabilities vary between $6,7 \times 10^{-5} \text{cms}^{-1}$ and $4,70 \times 10^{-8} \text{cms}^{-1}$ for the argillaceous soils, and $1,6 \times 10^{-3} \text{cms}^{-1}$ and $1,7 \times 10^{-3} \text{cms}^{-1}$ for the gravelly soil. Calculated material permeabilities based on the material grading characteristics, vary between $1,07 \times 10^{-4} \text{cms}^{-1}$ and $8,9 \times 10^{-8} \text{cms}^{-1}$ for the argillaceous soils, and $1,7 \times 10^{-2} \text{cms}^{-1}$ and $4,0 \times 10^{-2} \text{cms}^{-1}$ for the gravelly soil.
- *Shear Characteristics* : The results of shear tests indicate the argillaceous materials to be cohesionless, with a peak angle of internal friction of $14,9^\circ$; and the cohesion of the gravelly soil to vary between $5,4 \text{kNm}^{-2}$ and $6,3 \text{kNm}^{-2}$, while the peak angle of internal friction varies between $30,2^\circ$ and $43,5^\circ$.

5.8.4 Material Excavability

In 15 of the 19 test pits excavated for the survey in this area, it was possible to penetrate past a depth of 2500mm without encountering refusal of excavation. In test pits 14, 15, 16 and 18 refusal of

excavation was encountered shallower than 2000mm on hard rock, shale. These test pits are all located in the western parts of the farmlands area.

5.8.5 Perched Groundwater

The presence of surface water, especially in the Cyferpan area, is common. Perched water occurs generally throughout the area and was encountered at depths usually deeper than 2500mm.

5.8.6 Pollution

No discernable signs of pollution were encountered.

6 CONCLUSIONS AND RECOMMENDATIONS

6.1 Existing Waste Site

If it is important to obtain information regarding depth to ground water in this area, it can be done, but at a cost. More expensive methods such as continuous flight augering or core drilling can be considered, but whether the cost to obtain such information is really worthwhile, is a question that should be addressed first.

6.2 New Dams

The materials present in this area vary according to origin. Towards the north it is more clayey and towards the south more silty. With selection and a more detailed investigation, the area can be divided into zones of materials suitable for impermeable liners or capping. When considering the use of this area for dam construction, cognizance must be taken of the fact that excavation will be limited due to the presence of rock at fairly shallow depths, especially in the southern part thereof.

6.3 New Waste Site

From the vegetation and presence of perched ground water in especially the highly permeable transported soil and pebblestone marker, it appears as if this area may originally have been part of a wetland. The effect of this must be taken into account when considering the establishment of a waste site here.

6.4 Existing Dams

The existence of these dams is a fact that must be accepted as part of the scenario. However, it is important to realize that visual signs of pollution are present in the transported soil and pebblestone

marker ; impermeable materials serving as a natural barrier between the dams and the environment have been removed for construction, and the contents of the dam are in contact with residual diabase. In the given hydro geological scenario the diabase serves as an aquifer and the contents of the dam can come in contact with the permanent ground water. A strong smell of tar in the residual soil was encountered up to 18000mm deep.

6.5 Perimeter Areas

Apart from the south eastern corner, the perimeter areas investigated appear to be fairly free of pollution and not really susceptible to pollution. However, in the south eastern corner of the site, soils occur as thick deposits of sand and sandstone. These materials do not serve as barriers limiting the progress of any water borne materials. Discernable signs of pollution were thus encountered in this area.

6.6 Cyferpan and Farmland Areas

It is believed that the Cyferpan area is too wet to develop as a borrow pit for the future construction. The farmlands area may be set aside for this purpose, but detailed soils investigations are required to delineate the argillaceous and gravelly materials. The suitability of this area is again limited by the presence of water at fairly shallow depths.



FJ Breytenbach, Pr Eng
For Soilkraft cc


9 May 2002


**ISCOR FLAT STEEL PRODUCTS VANDERBIJL
PARK : PROPOSED MASTER PLAN FOR WASTE
MANAGEMENT - FINAL GEOTECHNICAL REPORT**

7 ADDENDUM A

TEST PIT PROFILES

Geotechnical sampling points







ISCOR
flat steel

NOTES:

- COORDINATE SYSTEM ACCORDING TO BOON LOCAL GRID (BLACK) 1:25 (LIGHT BLUE)
- EXISTING GEOTECHNICAL PROFILES
- EXISTING PLAN AUGER HOLES
- EXISTING PLAN TEST PITS

Draft for discussion
CONFIDENTIAL
Research for I/S



OCKIE FOURIE
CONSULTING ENGINEERS
(Pty) Ltd

PROJECT

ISCOR
VANDERBIJLPARK STEEL:
MASTER PLAN

DRAWING TITLE

GEOTECHNICAL

DATE

NOVEMBER 2011

SCALE

1:750

VAN RENSSSEN & FORTUIN
CONSULTING ENGINEERS
RACCOMENDING ENGINEERING
BAGWATLOLO BA CHABURHWE



HEAD OFFICES AT:
PRETORIA

P.O. BOX 1078 PRETORIA 0001
TEL: 011 333 1000
FAX: 011 333 1001
E-MAIL: info@vrf.co.za
WEB: www.vrf.co.za

C/R	C/S
DRAWN	CHECKED
JvdW	AO
APPROVED FOR CONSTRUCTION	CHECKED

DATE: _____

FIGURE 1



CLIENT APPROVAL

SIGNATURE: _____

NAME: _____ DATE: _____

FOR INFORMATION



PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	1	SHEET No: Vel Nr:	1
SITE: TERREIN:	Proposed New Dam Site	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	23 March 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 40' 05,6" S 27° 47' 22,6" E		

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
	0,30	Slightly moist, light grey, loose, intact, silty <u>SAND</u> . Fine colluvium.	
	0,50	Slightly moist, light yellow grey mottled light brown, loose, intact, silty <u>SAND</u> and matrix supported, rounded, black, ferricrete concretions. Ferruginized pebblestone marker.	
	1,00	Slightly moist, light yellow mottled light brown, medium dense, ferruginized, clayey <u>SAND</u> and matrix supported, fine, subrounded, gravels of ferricrete. Ferruginized residual shale.	
	1,50	Moist, light brown stained black on discontinuities, firm, relic jointed, clayey <u>SILT</u> . Residual shale.	
	2,20	Light brown mottled black on fractures, very closely fractured, very fine grained, slightly weathered, soft rock, <u>SHALE</u> . Discontinuities are closed, smooth and clean.	
		Water encountered Water teëgekorn	NOTES / NOTAS 1 Excavation terminated at 2200mm due to slow progress. 2 No seepage encountered.
		Water level Watervlak	
		Bottom of hole Bodem van gat	
		Approximate material change Benaderde materiaalverandering	
		Disturbed sample Versteurde monster	
		Undisturbed sample Onversteurde monster	
		Consolidation sample Konsolidasie monster	
		Indicator tests Klassifikasie toets	
		Contractor: Kontrakteur:	
		Date Drilled: Datum Geboor:	
		Machine: Masjien:	
		Hole diameter: Gat deursnee:	
		Water depth: Watervlak:	


**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 1

FIG A1

Draft for discussion
CONFIDENTIAL
Research for IVS

PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	2	SHEET No: Vel Nr:	1
SITE: TERREIN:	Proposed New Dam Site	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	23 March 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 40' 13,7" S 27° 47' 28,5" E		



	Water encountered Water teëgekorn	Contractor: Kontrakteur:	Vuma Construction	NOTES / NOTAS 1 Excavation terminated to facilitate percolation test. 2 No seepage encountered. 3 No percolation encountered at bottom of the test pit in standard percolation test.
	Water level Waternusvlak	Date Drilled: Datum Geboor:	4 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Caterpillar 416C	
	Approximate material change Benaderde materiaalverandering	Hole diameter: Gat deursnee:	600mm	
	Disturbed sample Versteurde monster	Water depth: Watervlak:		
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests Klassifikasie toets			

SOIL KRAFT	SOIL PROFILE : TEST PIT 2	FIG A2
-----------------------	----------------------------------	---------------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	3	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	25 March
TERREIN:	Proposed New Dam Site	BESKRYF:		DATUM:	2002
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 40' 01,6" S		
KLIENT:		POSISIE:	27° 47' 40,9" E		

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
	0,30	Slightly moist, light grey, loose, intact, silty <u>SAND</u> . Fine colluvium.	
	0,90	Slightly moist, dark yellow, loose, intact, silty <u>SAND</u> . Fine colluvium.	
	1,70	Slightly moist, pale light grey mottled dark yellow, stiff, intact, clayey <u>SILT</u> and matrix supported, fine subrounded, black ferricrete concretions. Residual shale.	
	2,40	Slightly moist, light brown mottled black, light grey and dark red brown, stiff to very stiff, cemented, clayey <u>SILT</u> . Residual shale.	
		Water encountered Water teëgekom	
		Water level Waternivoo	
		Bottom of hole Bodem van gat	
		Approximate material change Benaderende materiaalverandering	
		Disturbed sample Versteurde monster	
		Undisturbed sample Onversteurde monster	
		Consolidation sample Konsolidasie monster	
		Indicator tests Klassifikasie toets	
		Contractor: Kontrakteur: Vuma Construction	NOTES / NOTAS 1 Excavation terminated at 2400mm due to slow progress. 2 No seepage encountered.
		Date Drilled: Datum Geboor: 4 March 2002	
		Machine: Masjien: Caterpillar 416C	
		Hole diameter: Gat deursnee: 600mm	
		Water depth: Watervlak:	


SOIL
KRAFT

SOIL PROFILE : TEST PIT 3

FIG A3

Draft for discussion
CONFIDENTIAL
Research for IVS




PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	4	SHEET No: Vel Nr:	1
SITE: TERREIN:	Proposed New Dam Site	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	25 March 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 39' 59,6" S 27° 47' 35,6" E		



	Water encountered Water teëgekorn	Contractor: Kontrakteur:	Vuma Construction	NOTES / NOTAS 1 Excavation terminated at 2600mm due to slow progress. 2 No seepage encountered.
	Water level Watervlaks	Date Drilled: Datum Geboor:	4 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Caterpillar 416C	
	Approximate material change Benaderde materiaalverandering	Hole diameter: Gat deursnee:	600mm	
	Disturbed sample Versteurde monster	Water depth: Watervlak:		
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests Klassifikasie toets			

Draft for discussion
CONFIDENTIAL
Research for IVS

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	5	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	25 March
TERREIN:	Proposed New Dam Site	BESKRYF:		DATUM:	2002
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 39' 57,6" S		
KLIENT:		POSISIE:	27° 47' 30,3" E		

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
	0,30	Moist, light grey brown, loose, intact, silty <u>SAND</u> . Fine colluvium.	
	1,70	Slightly moist, light grey, firm, intact, sandy <u>CLAY</u> . Residual shale.	
	2,50	Slightly moist, pale light grey mottled dark yellow, firm, intact, sandy <u>SILT</u> . Residual shale.	
	3,00	Pale light brown mottled light grey, very closely fractured, very fine grained, moderately weathered, soft rock, <u>SHALE</u> . Discontinuities are open, smooth and clean.	
	Water encountered Water trefgekom	Contractor: Kontrakteur:	NOTES / NOTAS 1 Excavation terminated at 3000mm due to slow progress. 2 No seepage encountered.
	Water level Waterpeilvlak	Date Drilled: Datum Geboor:	
	Bottom of hole Bodem van gat	Machine: Masjien:	
	Approximate material change Benaderde materiaalverandering	Hole diameter: Gat deursnee:	
	Disturbed sample Versteurde monster	Water depth: Watervlak:	
	Undisturbed sample Onversteurde monster		
	Consolidation sample Konsolidasie monster		
	Indicator tests Klassifikasie toets		


**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 5

FIG A5

Draft for discussion
CONFIDENTIAL
Research for IYS

PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	6	SHEET No: Vel Nr:	1
SITE: TERREIN:	Proposed New Dam Site	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	25 March 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 39' 55,4" S 27° 47' 24,9" E		



	Water encountered Water teëgekrom	Contractor: Kontrakteur:	Vuma Construction	NOTES / NOTAS 1 Excavation terminated at 2700mm due to slow progress. 2 No seepage encountered.
	Water level Watervlvlak	Date Drilled: Datum Geboor:	4 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Caterpillar 416C	
	Approximate material change Benaderde materiaalverandering	Hole diameter: Gat deursnee:	600mm	
	Disturbed sample Versteurde monster	Water depth: Watervlak:		
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests Klassifikasie toets			


**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 6

FIG A6

Draft for discussion
CONFIDENTIAL
Research for IWS

PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	7	SHEET No: Vel Nr:	1
SITE: TERREIN:	Proposed New Dam Site	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	27 March 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 39' 53,0" S 27° 47' 26,2" E		




**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 7

FIG A7

PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	8	SHEET No. Vel Nr:	1
SITE: TERREIN:	Proposed New Dam Site	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	27 March 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 39' 53,3" S 27° 47' 20,0" E		

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
		Slightly moist, light grey, firm, intact, sandy CLAY . Residual diabase.	
	0,90	Slightly moist, light yellow grey, firm, intact, sandy CLAY . Residual diabase.	
	1,30	Slightly moist, pale light grey, firm, slickensided, clayey SILT and matrix supported, subangular, coarse, soft, white, calcareous concretions. Residual diabase.	
	2,70		
	Water encountered Water toegekom	Contractor: Kontrakteur:	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 No seepage encountered.
	Water level Waternusvlak	Date Drilled: Datum Geboor:	
	Bottom of hole Bodem van gat	Machine: Masjien:	
	Approximate material change Benaderde materiaalverandering	Hole diameter: Gat deursnee:	
	Disturbed sample Versteurde monster	Water depth: Watervlak:	
	Undisturbed sample Onversteurde monster		
	Consolidation sample Konsolidasie monster		
	Indicator tests Klassifikasie toets		


Draft for discussion
 CONFIDENTIAL
 Research for IVS

**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 8

FIG A8

PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	9	SHEET No: Vel Nr:	1
SITE: TERREIN:	Proposed New Oam Site	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	28 March 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 39' 40,4" S 27° 47' 24,9" E		



	Water encountered Water teëgekorn	Contractor: Kontrakteur:	Vuma Construction	NOTES / NOTAS 1 Refusal of excavation at 2000mm due to slow progress. 2 No seepage encountered.
	Water level Watervlaks	Date Drilled: Datum Geboor:	4 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Caterpillar 416C	
	Approximate material change Benaderde materiaalverandering	Hole diameter: Gat deursnee:	600mm	
	Disturbed sample Versteurde monster	Water depth: Watervlak:		
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests Klassifikasie toets			

**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 9


FIG A9

Draft for discussion
 CONFIDENTIAL
 Research for VS

PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	10	SHEET No: Vel Nr:	1
SITE: TERREIN:	Proposed New Dam Site	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	28 March 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 39' 43,1" S 27° 47' 36,3" E		

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL		Sample Monster
		Slightly moist, light grey, very loose, intact, silty <u>SAND</u> . Fine colluvium.		
	0,60	Slightly moist, light yellow mottled light grey, soft, intact, sandy <u>SILT</u> . Residual diabase.		
	1,00	Slightly moist, light brown mottled light grey speckled black, firm, ferruginized, sandy <u>CLAY</u> and matrix supported, fine, rounded, black, ferricrete concretions. Residual diabase.		
	1,60	Slightly moist, light grey mottled pale light yellow, stiff, intact, clayey <u>SILT</u> . Residual diabase.		
	2,20			
	Water encountered Water teëgekorn		Contractor: Kontrakteur:	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 No seepage encountered. 3 No seepage encountered in standard percolation test.
	Water level Watervlaks		Date Drilled: Datum Geboor:	
	Bottom of hole Bodem van gat		Machine: Masjien:	
	Approximate material change Benaderde materiaalverandering		Hole diameter: Gat deursnee:	
	Disturbed sample Versteurde monster		Water depth: Watervlak:	
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests Klassifikasie toets			

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	11	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	28 March
TERREIN:	Proposed New Dam Site	BESKRYF:		DATUM:	2002
CLIENT:		LOCATION:	26° 39' 41,2" S		
KLIENT:	Van Renssen & Fortuin	POSISIE:	27° 47' 47,8" E		




**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 11

FIG A11

Draft for discussion
 CONFIDENTIAL
 Research for W&S

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	1	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:	Proposed New Waste Site	LOGGED BY:	FJB	DATE:	27 March
TERREIN:		BESKRYF:		DATUM:	2002
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 38,5" S		
KLIENT:		POSISIE:	27° 49' 03,5" E		




**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 1

FIG A12


PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	2	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	1 April 2002
TERREIN:	Proposed New Waste Site	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 30,1" S		
KLIENT:		POSISIE:	27° 49' 02,7" E		



	Water encountered Water teengekorn	Contractor: Kontrakteur:	Vuma Construction	NOTES / NOTAS 1 Excavation terminated due to continuous collapse of test pit side walls. 2 Very strong seepage encountered between 1000mm and 1900mm. 3 Refusal of excavation not encountered.
	Water level Waterpeilvlak	Date Drilled: Datum Geboor:	5 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Caterpillar 416C	
	Approximate material change Benaderende materiaalverandering	Hole diameter: Gat deursnee:	600mm	
	Disturbed sample Versteurde monster	Water depth: Watervlak:		
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests			

SOIL KRAFT	SOIL PROFILE : TEST PIT 2	FIG A13
-----------------------	----------------------------------	----------------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	3	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	1 April 2002
TERREIN:	Proposed New Waste Site	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 28,9" S		
KLIJENT:		POSISIE:	27° 48' 54,0" E		




	Water encountered Water teëskom	Contractor: Vuma Construction	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 Seepage encountered between 500mm and 600mm.
	Water level Waterpeilvlak	Contracteur:	
	Bottom of hole Bodem van gat	Date Drilled: 5 March 2002 Datum Geboor:	
	Approximate material change Benaderende materiaalverandering	Machine: Caterpillar 416C Masjien:	
	Disturbed sample Versteurde monster	Hole diameter: 600mm Gat deursnee:	
	Undisturbed sample Onversteurde monster	Water depth: Watervlak:	
	Consolidation sample Konsolidasie monster		
	Indicator tests		

**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 3

FIG A14


PROJECT: Master Plan for Pollution Control - Iscor	TRAIL HOLE: 4	SHEET No: 1
PROJEK: Vanderbijl Park	TOETSGAT: 4	Vel Nr: 1
SITE: Proposed New Waste Site	LOGGED BY: FJB	DATE: 1 April 2002
TERREIN: Proposed New Waste Site	BESKRYF: FJB	DATUM: 1 April 2002
CLIENT: Van Renssen & Fortuin	LOCATION: 26° 38' 32,8" S	
KLIENT: Van Renssen & Fortuin	POSISIE: 27° 48' 55,5" E	



	Water encountered Water teëgekrom	Contractor: Vuma Construction	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 Very strong seepage encountered between 1100mm and 1900mm.
	Water level Waterpeilvlak	Date Drilled: 5 March 2002	
	Bottom of hole Bodem van gat	Datum Geboor:	
	Approximate material change Benaderende materiaalverandering	Machine: Caterpillar 416C	
	Disturbed sample Versteurde monster	Masjien:	
	Undisturbed sample Onversteurde monster	Hole diameter: 600mm	
	Consolidation sample Konsolidasie monster	Gat deursnee:	
	Indicator tests	Water depth: Watervlak:	


SOIL KRAFT	SOIL PROFILE : TEST PIT 4	FIG A15
-------------------	----------------------------------	----------------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	5	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	1 April 2002
TERREIN:	Proposed New Waste Site	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 41,7" S		
KLIENT:		POSISIE:	27° 48' 55,2" E		



SOIL KRAFT	SOIL PROFILE : TEST PIT 5	FIG A16
-----------------------	----------------------------------	----------------

PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	6	SHEET No: Vel Nr:	1
SITE: TERREIN:	Proposed New Waste Site	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	1 April 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 38' 28,9" S 27° 48' 44,4" E		




	Water encountered Water teengekorn	Contractor: Kontrakteur:	Vuma Construction	NOTES / NOTAS 1 Test pit abandoned due to very strong seepage. 2 Very strong seepage encountered between 600mm and surface.
	Water level Waterpeilvlak	Date Drilled: Datum Geboor:	5 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Caterpillar 416C	
	Disturbed sample Versteurde monster	Hole diameter: Gat deursnee:	600mm	
	Undisturbed sample Onversteurde monster	Water depth: Watervlak:		
	Consolidation sample Konsolidasie monster			
	Indicator tests			

**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 6

FIG A17

PROJECT: Master Plan for Pollution Control - Iscor	TRAIL HOLE: 7	SHEET No: 1
PROJEK: Vanderbijl Park	TOETSGAT:	Vel Nr:
SITE: Proposed New Waste Site	LOGGED BY: FJB	DATE: 1 April 2002
TERREIN:	BESKRYF:	DATUM:
CLIENT: Van Renssen & Fortuin	LOCATION: 26° 38' 28,8" S	
KLIENT:	POSISIE: 27° 49' 05,7" E	




	Water encountered Water teëgekorn	Contractor: Vuma Construction	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 Very strong seepage encountered between 1100mm and 1900mm.
	Water level Waterpeilvlak	Date Drilled: 5 March 2002	
	Bottom of hole Bodem van gat	Datum Geboor:	
	Approximate material change Benaderende materiaalverandering	Machine: Caterpillar 416C	
	Disturbed sample Versteurde monster	Masjien:	
	Undisturbed sample Oorversteurde monster	Hole diameter: 600mm	
	Consolidation sample Konsolidasie monster	Gat deursnee:	
	Indicator tests	Water depth: Watervlak:	

**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 7

FIG A18

PROJECT: Master Plan for Pollution Control - Iscor	TRAIL HOLE: 1	SHEET No: 1
PROJEK: Vanderbijl Park	TOETSGAT:	Vel Nr:
SITE: Existing Dams	LOGGED BY: FJB	DATE: 1 April 2002
TERREIN:	BESKRYF:	DATUM:
CLIENT: Van Renssen & Fortuin	LOCATION: 26° 38' 38,5" S	
KLIENT:	POSISIE: 27° 49' 03,5" E	



Water encountered Water teëgekorn Water level Watervlakte Bottom of hole Bodem van gat Approximate material change Benaderende materiaalverandering Disturbed sample Versteurde monster Undisturbed sample Onversteurde monster Consolidation sample Konsolidasie monster Indicator tests	Contractor: Vuma Construction Kontrakteur: Date Drilled: 5 March 2002 Datum Geboor: Machine: Caterpillar 416C Masjien: Hole diameter: 600mm Gat deursnee: Water depth: Watervlak:	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 Very strong seepage encountered between 1400mm and 2100mm.
---	--	--


SOIL KRAFT	SOIL PROFILE : TEST PIT 1	FIG A19
-------------------	----------------------------------	----------------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	2	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	1 April 2002
TERREIN:	Existing Dams	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 38,5" S		
KLIENT:		POSISIE:	27° 49' 03,5" E		

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
		Dry, light brown, medium dense, intact, silty <u>SAND</u> . Fine colluvium.	
	0,50		
	0,70	Dry, light brown, medium dense, intact, silty <u>SAND</u> and matrix supported, coarse, subrounded and rounded, gravels and cobbles of quartzitic sandstone. Pebblestone marker.	
	1,40	Slightly moist, light brown, loose, intact, silty <u>SAND</u> and matrix supported, fine, rounded, ferricrete nodules. Residual quartzitic sandstone.	
	2,30	Slightly moist, dark red brown mottled dark yellow, very dense, cemented, silty <u>SAND</u> and matrix supported, subrounded and subangular, coarse gravels and cobbles of quartzitic sandstone. Ferruginized residual quartzitic sandstone.	
	Water encountered Water teengekorn	Contractor: Kontrakteur:	NOTES / NOTAS 1 Refusal of excavation at 2300mm on hard rock, quartzitic sandstone. 2 No seepage encountered.
	Water level Water vlak	Date Drilled: Datum Geboor:	
	Bottom of hole Bodem van gat	Machine: Masjien:	
	Approximate material change Benaderende materiaalverandering	Hole diameter: Gat deursnee:	
	Disturbed sample Versteurde monster	Water depth: Watervlak:	
	Undisturbed sample Onversteurde monster		
	Consolidation sample Konsoliderings monster		
	Indicator tests		

SOIL KRAFT	SOIL PROFILE : TEST PIT 2	FIG A20
-----------------------	----------------------------------	----------------


PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	3	SHEET No: Vel Nr:	1
SITE: TERREIN:	Existing Dams	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	1 April 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 38' 59,7" S 27° 49' 37,7" E		



	Water encountered Water teëgekorn	Contractor: Kontrakteur:	Vuma Construction	NOTES / NOTAS 1 Refusal of excavation at 2400mm on very dense, ferruginized, quaternary gravels. 2 Very strong seepage encountered between 1200mm and 1900mm. 3 In-situ materials smell very strongly of tar.
	Water level Waterpeilvlak	Date Drilled: Datum Geboor:	5 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Caterpillar 416C	
	Approximate material change Benaderende materiaalverandering	Hole diameter: Gat deursnee:	600mm	
	Disturbed sample Versteurde monster	Water depth: Watervlak:		
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests			

SOIL KRAFT	SOIL PROFILE : TEST PIT 3	FIG A21
-----------------------	----------------------------------	----------------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	4	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:	Existing Dams	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 59,0" S		
KLIENT:		POSISIE:	27° 49' 51,7" E		



	Water encountered Water teëgekom	Contractor: Vuma Construction	NOTES / NOTAS 1 Refusal of excavation at 1300mm on very dense, ferruginized, quaternary gravels. 2 Very strong seepage encountered between 1000mm and 1200mm. 3 In-situ materials smell very strongly of tar.
	Water level Waterusvlak	Kontrakteur:	
	Bottom of hole Bodem van gat	Date Drilled: 5 March 2002 Datum Geboor:	
	Approximate material change Benaderde materiaalverandering	Machine: Caterpillar 416C Masjien:	
	Disturbed sample Versteurde monster	Hole diameter: 600mm Gat deursnee:	
	Undisturbed sample Onversteurde monster	Water depth: Watervlak:	
	Consolidation sample Konsolidasie monster		
	Indicator tests		


SOIL KRAFT	SOIL PROFILE : TEST PIT 4	FIG A22
-----------------------	----------------------------------	----------------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	6	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:	Existing Dams	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 37' 58,0" S		
KLIENT:		POSISIE:	27° 50' 04,3" E		

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
		Very moist, light yellow brown, loose, intact (polluted ?), silty <u>SAND</u> . Fine colluvium.	
	0,70 0,80 0,90	Abundant clast supported, medium coarse, rounded, <u>GRAVELS</u> of ferricrete in a matrix of light yellow brown, silty sand. Overall consistency is dense. Ferruginized fine colluvium.	 Lab no 4600
		Abundant, clast supported, rounded, <u>COBBLES</u> of chert, quartz and quartzite in a matrix of dark yellow mottled dark red blotched black, hardpan pedocretes. Overall consistency is dense. Ferruginized quaternary gravels.	
	Water encountered Water toëskom	Contractor: Kontrakteur:	NOTES / NOTAS 1 Refusal of excavation encountered at 900mm on very dense, ferruginized, quaternary deposits. 2 Seepage encountered between 800mm and 900mm. 3 In-situ materials smell very strongly of tar.
	Water level Watervlak	Date Drilled: Datum Geboor:	
	Bottom of hole Bodem van gat	Machine: Masjien:	
	Approximate material change Benaderende materiaalverandering	Hole diameter: Gat deursnee:	
	Disturbed sample Versteurde monster	Water depth: Watervlak:	
	Undisturbed sample Onversteurde monster		
	Consolidation sample Konsoliderings monster		
	Indicator tests		

SOIL KRAFT	SOIL PROFILE : TEST PIT 6	FIG A24
---------------	---------------------------	---------


PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	7	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:	Existing Dams	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 37' 16,4" S		
KLIENT:		POSISIE:	27° 49' 49,7" E		



	Water encountered Water teëgekorn	Contractor: Kontrakteur:	Vuma Construction	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 Seepage encountered between 1100mm and 1500mm.
	Water level Waterpeilvlak	Date Drilled: Datum Geboor:	6 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Caterpillar 416C	
	Approximate material change Benaderende materiaalverandering	Hole diameter: Gat deursnee:	600mm	
	Disturbed sample Versteurde monster	Water depth: Watervlak:		
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests			

SOIL KRAFT	SOIL PROFILE : TEST PIT 7	FIG A25
-----------------------	----------------------------------	----------------


PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	8	SHEET No:	1
SITE: TERREIN:	Existing Dams	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	2 April 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 37' 39,6" S 27° 49' 38,7" E		



	Water encountered Water trefskom	Contractor: Kontrakteur:	Vuma Construction	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 Seepage encountered at 1600mm.
	Water level Waternivvlak	Date Drilled: Datum Geboor:	6 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Caterpillar 416C	
	Approximate material change Benaderde materiaalverandering	Hole diameter: Gat deursnee:	600mm	
	Disturbed sample Versteurde monster	Water depth: Waternvlak:		
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests			

SOIL KRAFT	SOIL PROFILE : TEST PIT 8	FIG A26
-----------------------	----------------------------------	----------------


PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	9	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:	Existing Dams	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 37' 29,1" S		
KLIENT:		POSISIE:	27° 49' 38,7" E		



	Water encountered Water teenekom	Contractor: Kontrakteur:	Vuma Construction	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 Very strong seepage between 1300mm and 2300mm. 3 Sidewalls collapse between 1300mm and 2300mm. Test pit abandoned.
	Water level Watervlakte	Date Drilled: Datum Geboor:	6 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Caterpillar 416C	
	Approximate material change Benaderde materiaalverandering	Hole diameter: Gat deursnee:	600mm	
	Disturbed sample Versteurde monster	Water depth: Watervlak:		
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests			

SOIL KRAFT	SOIL PROFILE : TEST PIT 9	FIG A27
-----------------------	----------------------------------	----------------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	1	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:	Perimeter Test Pits	LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 39' 17,5" S		
KLIENT:		POSISIE:	27° 48' 10,3" E		



SOIL
KRAFT

SOIL PROFILE : TEST PIT 1

FIG A29


PROJECT: Master Plan for Pollution Control - Iscor		TRAIL HOLE: 2	SHEET No: 1
PROJEK: Vanderbijl Park		TOETSGAT:	Vel Nr:
SITE: Perimeter Test Pits		LOGGED BY: FJB	DATE: 2 April 2002
TERREIN:		BESKRYF:	DATUM:
CLIENT: Van Renssen & Fortuin		LOCATION: 26° 39' 33,8" S	
KLIENT:		POSISIE: 27° 48' 02,2" E	

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
		FILL : Consisting of slightly moist, pale light grey, soft, sandy clay.	
	0,60	Slightly moist, light grey becoming light brown, loose, pinhole voided, silty SAND . Fine colluvium.	
	1,00		
	1,30	Slightly moist, light brown becoming dark yellow, loose, intact, silty SAND . Fine colluvium.	
	1,90	Slightly moist, dark yellow speckled black, medium dense, ferruginized, silty SAND and matrix supported, medium coarse, black, ferricrete concretions. Reworked residual diabase ?	
	2,60	Slightly moist, dark yellow mottled light grey speckled black, stiff, slickensided and ferruginized, silty CLAY . Residual diabase.	

	Water encountered Water teenekom	Contractor: Kontrakteur: Vuma Construction	NOTES / NOTAS 1 Refusal of excavation at 2600mm due to slow progress. 2 No seepage encountered.
	Water level Waternivoo	Date Drilled: Datum Geboor: 11 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien: Caterpillar 416C	
	Approximate material change Benaderde materiaalverandering	Hole diameter: Gat deursnee: 600mm	
	Disturbed sample Versteurde monster	Water depth: Waternivoo:	
	Undisturbed sample Onversteurde monster		
	Consolidation sample Konsolidasie monster		
	Indicator tests		


SOIL KRAFT	SOIL PROFILE : TEST PIT 2	FIG A30
---------------	---------------------------	---------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	3	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vol Nr:	
SITE:	Perimeter Test Pits	LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 39' 07,7" S		
KLIENT:		POSISIE:	27° 48' 12,6" E		




SOIL KRAFT	SOIL PROFILE : TEST PIT 3	FIG A31
---------------	---------------------------	---------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	4	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vol Nr:	
SITE:		LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:	Perimeter Test Pits	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 56,2" S		
KLIENT:		POSISIE:	27° 48' 14,9" E		



SOIL KRAFT	SOIL PROFILE : TEST PIT 4	FIG A32
---------------	---------------------------	---------


PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	5	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:	Perimeter Test Pits	LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 44,3" S		
KLIENT:		POSISIE:	27° 48' 17,1" E		



	Water encountered Water teëskoon	Contractor: Kontrakteur:	Vuma Construction	NOTES / NOTAS 1 Refusal of excavation at 1500mm on very dense, hardpan ferricrete. 2 No seepage encountered.
	Water level Waterpeil	Date Drilled: Datum Geboor:	11 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Caterpillar 416C	
	Approximate material change Benaderde materiaalverandering	Hole diameter: Gat deursnee:	600mm	
	Disturbed sample Versteurde monster	Water depth: Watervlak:		
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests			


SOIL KRAFT	SOIL PROFILE : TEST PIT 5	FIG A33
---------------	---------------------------	---------

PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	6	SHEET No: Vel Nr:	1
SITE: TERREIN:	Perimeter Test Pits	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	2 April 2002
CLIENT: KLIJNT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 38' 31,9" S 27° 48' 21,1" E		



SOIL KRAFT	SOIL PROFILE : TEST PIT 6	FIG A34
---------------	---------------------------	---------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	7	SHEET No:	1
PROJEK:	Vanderbiil Park	TOETSGAT:		Vel Nr:	
SITE:	Perimeter Test Pits	LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 19,9" S		
KLIENT:		POSISIE:	27° 48' 24,9" E		

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
	1,10	Dark brown mottled black, very dense, honeycombe <u>FERRICRETE</u> Pedocretic deposits. Voids are open and filled with light grey clay.	
		Water encountered Water tesgekom	NOTES / NOTAS 1 Refusal of excavation encountered at 1100mm on very dense pedocretes. 2 No seepage encountered.
		Water level Waterusvlak	
		Bottom of hole Bodem van gat	
		Approximate material change Benaderende materiaalverandering	
		Disturbed sample Versteurde monster	
		Undisturbed sample Onversteurde monster	
		Consolidation sample Konsolidasie monster	
		Indicator tests	
		Contractor: Vuma Construction Kontrakteur: Date Drilled: 11 March 2002 Datum Geboor: Machine: Caterpillar 416C Masjien: Hole diameter: 600mm Gat deursnee: Water depth: Waternvlak:	

SOIL KRAFT	SOIL PROFILE : TEST PIT 7	FIG A35
---------------	---------------------------	---------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	8	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:	Perimeter Test Pits	LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 37' 57,8" S		
KLIENT:		POSISIE:	27° 48' 31,5" E		

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
	0,60	Moist, black, soft, intact, sandy <u>CLAY</u> . Fine colluvium.	
	2,00	Moist, light yellow grey, soft, intact, sandy <u>CLAY</u> . Residual diabase.	
	2,70	Slightly moist, pale light grey mottled dark yellow, stiff, slickensided, silty <u>CLAY</u> and matrix supported, fine rounded, ferricrete nodules. Residual diabase.	
		Water encountered Water in die put	
		Water level Water vlak	
		Bottom of hole Bodem van gat	
		Approximate material change Benaderende materiaalverandering	
		Disturbed sample Versteurde monster	
		Undisturbed sample Onversteurde monster	
		Consolidation sample Konsolidasie monster	
		Indicator tests	
		Contractor: Vuma Construction Kontrakteur:	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 Seepage not encountered.
		Date Drilled: 11 March 2002 Datum Geboor:	
		Machine: Caterpillar 416C Masjien:	
		Hole diameter: 600mm Gat deursnee:	
		Water depth: Watervlak:	


SOIL KRAFT	SOIL PROFILE : TEST PIT 8	FIG A36
---------------	---------------------------	---------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	9	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:	Perimeter Test Pits	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 37' 47,2" S		
KLIENT:		POSISIE:	27° 48' 12,1" E		

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
		<u>FILL</u> : Consisting of coarse, granulated slag. Road construction layerworks.	
	0,60		
		Very moist, black, soft, intact, sandy <u>CLAY</u> . Fine colluvium.	
	1,20		
		Very moist, pale light grey, soft, intact, sandy <u>CLAY</u> . Residual diabase.	
	1,70		
		Moist, pale light grey, very soft, slickensided, silty <u>CLAY</u> . Residual diabase.	
	2,60		
		Water encountered Water teëgekoms	
		Water level Waterpeil	
		Bottom of hole Bodem van gat	
		Approximate material change Benaderende materiaalverandering	
		Disturbed sample Versteurde monster	
		Undisturbed sample Onversteurde monster	
		Consolidation sample Konsolidasie monster	
		Indicator tests	
		Contractor: Vuma Construction Kontrakteur:	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 Seepage not encountered.
		Date Drilled: 11 March 2002 Datum Geboor:	
		Machine: Caterpillar 416C Masjien:	
		Hole diameter: 600mm Gat deursnee:	
		Water depth: Watervlak:	


SOIL KRAFT	SOIL PROFILE : TEST PIT 9	FIG A37
---------------	---------------------------	---------

PROJECT:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE:	10	SHEET No:	1
PROJEK:		TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:		DATE:	
TERREIN:		BESKRYF:		DATUM:	
	Perimeter Test Pits		FJB		2 April 2002
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 37' 54,5" S		
KLIENT:		POSISIE:	27° 48' 58,7" E		



SOIL KRAFT	SOIL PROFILE : TEST PIT 10	FIG A38
-----------------------	-----------------------------------	----------------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	11	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vol Nr:	
SITE:	Perimeter Test Pits	LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 37' 56,0" S		
KLIENT:		POSISIE:	27° 48' 48,3" E		



**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 11


FIG A39

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	12	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:	Perimeter Test Pits	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 39' 28,8" S		
KLIENT:		POSISIE:	27° 50' 25,6" E		

Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
	0,60	Slightly moist, light brown, loose, intact, silty <u>SAND</u> . Fine colluvium.	
	1,50	Slightly moist, light yellow, loose, intact, silty <u>SAND</u> and matrix supported, subangular, medium coarse, gravels of ferricrete and subrounded coarse gravels of quartzite. Pebblestone marker ?	
	2,20	Moist, dark red mottled dark yellow speckled black, very dense, ferruginized, silty <u>SAND</u> and matrix supported, coarse angular gravels of quartzite and rounded cobbles of quartz, quartzite and chert. Ferruginized quaternary gravels.	▽
Water encountered Water teëgestom		Contractor: Kontrakteur:	NOTES / NOTAS 1 Refusal of excavation encountered at 2200mm on very dense quaternary gravels. 2 Seepage encountered at 1500mm to 1700mm.
Water level Water vlak		Date Drilled: Datum Geboor:	
Bottom of hole Bodem van gat		Machine: Masjien:	
Approximate material change Benaderende materiaalverandering		Hole diameter: Gat deursnee:	
Disturbed sample Versteurde monster		Water depth: Watervlak:	
Undisturbed sample Onversteurde monster			
Consolidation sample Konsolidasie monster			
Indicator tests			


SOIL KRAFT	SOIL PROFILE : TEST PIT 12	FIG A40
---------------	----------------------------	---------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	13	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:	Perimeter Test Pits	LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 39' 29,2" S		
KLIENT:		POSISIE:	27° 50' 16,9" E		



SOIL KRAFT	SOIL PROFILE : TEST PIT 13	FIG A41
---------------	----------------------------	---------

PROJECT: PROJEK:	Master Plan for Pollution Control - Iscor Vanderbijl Park	TRAIL HOLE: TOETSGAT:	14	SHEET No: Vel Nr:	1
SITE: TERREIN:	Perimeter Test Pits	LOGGED BY: BESKRYF:	FJB	DATE: DATUM:	2 April 2002
CLIENT: KLIENT:	Van Renssen & Fortuin	LOCATION: POSISIE:	26° 40' 14,7" S 27° 48' 52,2" E		




**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 14

FIG A42

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	15	SHEET No:	1
PROJEC:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:	Perimeter Test Pits	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 40' 23,6" S		
KLIENT:		POSISIE:	27° 49' 33,0" E		



SOIL KRAFT	SOIL PROFILE : TEST PIT 15	FIG A43
---------------	----------------------------	---------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	16	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vol Nr.	
SITE:		LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:	Perimeter Test Pits	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 40' 23,6" S		
KLIENT:		POSISIE:	27° 49' 46,0" E		


Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
		Very moist becoming wet, light brown, very loose, intact, silty SAND . Fine colluvium.	
	1,90	Very moist becoming wet, light brown, very loose, intact, silty SAND and matrix supported, rounded, medium coarse fericrete gravels. Fine colluvium.	
	2,60		
	Water encountered	Contractor:	NOTES / NOTAS 1 Refusal of excavation not encountered. 2 Seepage encountered at 1700mm. 3 Test pit side wall collapse from 1600mm.
	Water level	Kontrakteur: Vuma Construction	
	Bottom of hole	Date Drilled:	
	Approximate material change	Datum Geboor: 12 March 2002	
	Disturbed sample	Machine:	
	Undisturbed sample	Masjien: Caterpillar 416C	
	Consolidation sample	Hole diameter:	
	Indicator tests	Gat deursnee: 600mm	
		Water depth:	
		Watervlak:	

**SOIL
KRAFT**

SOIL PROFILE : TEST PIT 16


FIG A44

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	18	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vel Nr:	
SITE:	Perimeter Test Pits	LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 40' 03,3" S		
KLIENT:		POSISIE:	27° 50' 14,6" E		




SOIL KRAFT	SOIL PROFILE : TEST PIT 18	FIG A46
---------------	----------------------------	---------

PROJECT:	Master Plan for Pollution Control - Iscor	TRAIL HOLE:	19	SHEET No:	1
PROJEK:	Vanderbijl Park	TOETSGAT:		Vol Nr:	
SITE:		LOGGED BY:	FJB	DATE:	2 April 2002
TERREIN:	Perimeter Test Pits	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 39' 05,7" S		
KLIENT:		POSISIE:	27° 50' 52,3" E		



SOIL KRAFT	SOIL PROFILE : TEST PIT 19	FIG A47
---------------	----------------------------	---------

Cyferpan and Farmlands Test Pits



Draft for discussion
CONFIDENTIAL
Research for IVS

NOTES

- 1) Disturbed sample S127 at 2.9m.
- 2) Water in bottom of hole.

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz

TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET


INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02

DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP1

Scale
1:15



Draft for discussion
CONFIDENTIAL
Research for IVS

NOTES

2) Water in bottom of hole.

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz

TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET


INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02

DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP2

Scale
1:15



Draft for discussion
CONFIDENTIAL
Research for IVS

NOTES

- 1) Disturbed sample OX100 at 2.85m.
- 2) Water in bottom of hole.

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02

ELEVATION :
X-COORD :
Y-COORD :

TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET

DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

HOLE No: TP3

Scale
1:15

0.00

Medium dense silty SAND.
Slightly moist, dark grey, intact,
transported.

1.10

Firm sandy CLAY.
Moist, dark yellowish orange with dark olive
mottled, intact, transported.

2.90

Draft for discussion
CONFIDENTIAL
Research for IVS

NOTES

2) Water in bottom of hole.

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fVZ

TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02
DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP4

Scale
1:15

0.00

Medium dense silty SAND.
Slightly moist, dark grey, intact,
transported.

1.10

Firm sandy CLAY.
Moist, light yellowish orange dark olive
mottled.

2.85

Draft for discussion
CONFIDENTIAL
Research for IVS


CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz
TYPE SET BY : zs
SETUP FILE : SOILLAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02
DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP5

Scale
1:15



NOTES

2) Water in bottom of hole.

Draft for discussion
CONFIDENTIAL
Research for IVS

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz

TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET


INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02

DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP6

Scale
1:15



0.00

Medium dense gravelly SAND.
Slightly moist, dark grey, intact,
transported.

0.50

Firm CLAY.
Moist, dark grey, intact, transported.

3.00

NOTES

2) Water in bottom of hole.

Draft for discussion
CONFIDENTIAL
Research for IVS

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz


TYPE SET BY : zs
SETUP FILE : SOILLAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02

DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP7



NOTES

- 1) Disturbed sample XXX2 at 2.9m
- 2) Water in bottom of hole.

Draft for discussion
CONFIDENTIAL
Research for IVS

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz
TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02
DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP8

Scale
1:15

0.00

Medium dense silty SAND.
Slightly moist, dark grey, intact,
transported.

0.95

Firm clayey GRAVEL with FERRICRETE.
Moist, light yellowish orange, intact,
transported.

2.80

Draft for discussion
CONFIDENTIAL
Research for IVS

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz

TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02

DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP9

SOILLAB

(PTY) LTD
Reg. No.
71/00112/07

SOILKRAFT
ISCOR

HOLE No: TP10

Sheet 1 of 1

JOB NUMBER: S02-193

Scale
1:15

0.00

Medium dense silty SAND.
Slightly moist, light yellowish orange,
intact transported.

0.70

Medium dense Pebble stone marker.
slightly moist, light yellowish orange,
intact, transported.

1.10

Medium dense sandy GRAVEL.
Slightly moist, reddish orange, intact,
transported.

NW19

2.70

NOTES

- 1) Disturbed sample NW19 at 2.70

Draft for discussion
CONFIDENTIAL
Research for IVS

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz
TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02
DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP10

SOILAB


(PTY) LTD
Reg. No.
71/00112/07

SOILKRAFT
ISCOR

HOLE No: TP11
Sheet 1 of 1

JOB NUMBER: S02-193

Scale
1:15



CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz


TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02
DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP11

Scale
1:15



Draft for discussion
CONFIDENTIAL
Research for IVS

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02


ELEVATION :
X-COORD :
Y-COORD :

TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET

DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

HOLE No: TP12

Scale
1:15



0.00

Medium dense silty SAND.
Slightly moist, light brown, intact,
transported.

0.05

Dense SHALE GRAVEL.
Slightly moist, light yellowish orange,
intact, transported.

2.60

Draft for discussion
CONFIDENTIAL
Research for IVS


CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fVZ
TYPE SET BY : zs
SETUP FILE : SOILLAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02
DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP13

Scale
1:10



NOTES

- 1) TLB refuse at 1.9m.

Draft for discussion
CONFIDENTIAL
Research for IVS

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz

TYPE SET BY : zs
SETUP FILE : SOILLAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02

DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP14

Scale
1:10

0.00

Medium dense silty SAND.
Moist, light brown, intact, transported.

0.60

Dense SHALE GRAVEL with FERRICRETE.
Moist Light yellowish orange, intact,
transported.

AB203

1.85

NOTES

- 1) Disturbed sample AB203 at 1.85m
- 2) TLB refuse at 1.85m

Draft for discussion
CONFIDENTIAL
Research for IVS

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02


ELEVATION :
X-COORD :
Y-COORD :

TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET

DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

HOLE No: TP15

Scale
1:10



NOTES

- 1) TLB refuse at 1.7m

Draft for discussion
CONFIDENTIAL
Research for IVS

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFIED BY : fvz
TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02
DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP16

Scale
1:15

0.00

Medium dense silty SAND.
Slightly moist , light brown, intact,
transport.

1.00

Firm CLAY.
Slightly moist, light olive, intact,
transported.

2.80

Draft for discussion
CONFIDENTIAL
Research for IVS


CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz
TYPE SET BY : zs
SETUP FILE : SOILLAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02
DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP17

Scale
1:10



NOTES

- 1) TLB refuse at 1.7m.

Draft for discussion
CONFIDENTIAL
Research for IVS


CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fvz
TYPE SET BY : zs
SETUP FILE : SOILAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02
DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP18

Scale
1:15



Draft for discussion
CONFIDENTIAL
Research for IVS

CONTRACTOR :
MACHINE :
DRILLED BY :
PROFILED BY : fVZ
TYPE SET BY : zs
SETUP FILE : SOILLAB_E.SET

INCLINATION :
DIAM :
DATE : 01-03-02
DATE : 19-03-02
DATE : 22/03/02 08:53
TEXT : C:\DOTPLOT\PROFILE\S02-193.TXT

ELEVATION :
X-COORD :
Y-COORD :

HOLE No: TP19


**ISCOR FLAT STEEL PRODUCTS VANDERBIJL
PARK : PROPOSED MASTER PLAN FOR WASTE
MANAGEMENT - FINAL GEOTECHNICAL REPORT**

8 ADDENDUM B

AUGER HOLE PROFILES


Draft for discussion
CONFIDENTIAL
Research for IVS

PROJECT:	Master Plan for Pollution Control - Iscor	AUGER HOLE:	1	SHEET No:	1
PROJEK:	Vanderbiil Park	AWEGAAR:		Vel Nr:	
SITE:	Southern Perimeter	LOGGED BY:	FJB	DATE:	3 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 40' 14,8" S		
KLIJNT:		POSISIE:	27° 48' 44,8" E		




SOIL KRAFT	SOIL PROFILE : AUGER HOLE 1	FIG B1
---------------	-----------------------------	--------

PROJECT:	Master Plan for Pollution Control - Iscor	AUGER HOLE:	2	SHEET No:	1
PROJEK:	Vanderbiil Park	AWEGAAR:		Vol Nr:	
SITE:		LOGGED BY:	FJB	DATE:	3 April 2002
TERREIN:	Southern Perimeter	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 40' 23,2" S		
KLIENT:		POSISIE:	27° 49' 56,5" E		




SOIL KRAFT	SOIL PROFILE : AUGER HOLE 2	FIG B2
-----------------------	------------------------------------	---------------

PROJECT:	Master Plan for Pollution Control - Iscor	AUGER HOLE:	3	SHEET No:	1
PROJEK:	Vanderbiil Park	AWEGAAR :		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	4 April 2002
TERREIN:	Southern Perimeter	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 39' 23,1" S		
KLIENT:		POSISIE:	27° 50' 33,3" E		




SOIL KRAFT	SOIL PROFILE : AUGER HOLE 3	FIG B3
---------------	-----------------------------	--------

PROJECT:	Master Plan for Pollution Control - Iscor	AUGER HOLE:	4	SHEET No:	1
PROJEK:	Vanderbiil Park	AWEGAAR:		Vel Nr:	
SITE:	Proposed New Waste Site	LOGGED BY:	FJB	DATE:	4 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 31,8" S		
KLIENT:		POSISIE:	27° 49' 08,4" E		




SOIL KRAFT	SOIL PROFILE : AUGER HOLE 4	FIG B4
---------------	-----------------------------	--------

PROJECT:	Master Plan for Pollution Control - Iscor	AUGER HOLE:	5	SHEET No:	1
PROJEK:	Vanderbiil Park	AWEGAAR:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	4 April 2002
TERREIN:	Existing Dams	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 12,8" S		
KLIENT:		POSISIE:	27° 49' 40,9" E		



SOIL KRAFT	SOIL PROFILE : AUGER HOLE 5	FIG B5
---------------	-----------------------------	--------


PROJECT:	Master Plan for Pollution Control - Iscor	AUGER HOLE:	6	SHEET No:	1
PROJEK:	Vanderbiil Park	AWEGAAR :		Vel Nr:	
SITE:	Existing Dams	LOGGED BY:	FJB	DATE:	4 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 37' 56,4" S		
KLIJENT:		POSISIE:	27° 49' 40,9" E		



	Water encountered Water teenekom	Contractor: Frankipile	NOTES / NOTAS
	Water level Waterpeilvlak	Kontrakteur:	
	Bottom of hole Bodem van gat	Date Drilled: 13 March 2002 Datum Geboor:	1 Refusal of drilling encountered at 18000mm on medium hard rock, diabase.
	Approximate material change Benaderende materiaalverandering	Machine: Williams Digger 11	2 Strong seepage encountered between 1300mm and 2900mm.
	Disturbed sample Versteurde monster	Masjien:	
	Undisturbed sample Onversteurde monster	Hole diameter: 750mm Gat deursnee:	3 All earth materials down to 18000mm smells strongly of tar.
	Consolidation sample Konsolidasie monster	Water depth: Watervlak:	
	Indicator tests		

SOIL KRAFT	SOIL PROFILE : AUGER HOLE 6	FIG B6
-----------------------	------------------------------------	---------------

PROJECT:	Master Plan for Pollution Control - Iscor	AUGER HOLE:	7	SHEET No:	1
PROJEK:	Vanderbil Park	AWEGAAR:		Vel Nr:	
SITE:	North Western Perimeter	LOGGED BY:	FJB	DATE:	4 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 39' 23,6" S		
KLIJNT:		POSISIE:	27° 48' 07,3" E		




SOIL KRAFT	SOIL PROFILE : AUGER HOLE 7	FIG B7
-----------------------	------------------------------------	---------------

PROJECT:	Master Plan for Pollution Control - Iscor	AUGER HOLE:	8	SHEET No:	1
PROJEK:	Vanderbiil Park	AWEGAAR:		Vel Nr:	
SITE:	North Western Perimeter	LOGGED BY:	FJB	DATE:	4 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 38' 55,4" S		
KLIENT:		POSISIE:	27° 48' 18,1" E		


Legend Legende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
		Moist, black, soft, intact, sandy/silty <u>CLAY</u> . Fine colluvium.	
	1,20		
		Moist, light grey streaked black, fissured, silty <u>CLAY</u> and matrix supported, medium coarse, angular, white calcereous concretions. Residual diabase.	
	3,00		
+++++		Dark yellow mottled black on discontinuities, closely fractured, fine grained, highly weathered, soft rock to medium hard rock, <u>DIABASE</u> . Discontinuities are open, slightly rough and clean.	
+++++	3,40		
Water encountered Water teëgekoms		Contractor: Frankpile Kontrakteur:	NOTES / NOTAS 1 Refusal of drilling encountered at 3400mm on medium hard rock, diabase. 2 Seepage encountered between 2800mm and 3000mm.
Water level Waterpeilvlak		Date Drilled: 14 March 2002 Datum Geboor:	
Bottom of hole Bodem van gat		Machine: Williams Digger 11 Masjien:	
Approximate material change Benaderende materiaalverandering		Hole diameter: 750mm Gat deursnee:	
Disturbed sample Versteurde monster		Water depth: Waternvlak:	
Undisturbed sample Onversteurde monster			
Consolidation sample Konsolidesie monster			
Indicator tests			

SOIL KRAFT	SOIL PROFILE : AUGER HOLE 8	FIG B8
---------------	-----------------------------	--------



SOIL KRAFT	SOIL PROFILE : AUGER HOLE 9	FIG B9
-----------------------	------------------------------------	---------------

PROJECT:	Master Plan for Pollution Control - Iscor	AUGER HOLE:	10	SHEET No:	1
PROJEK:	Vanderbil Park	AWEGAAR:		Vel Nr:	
SITE:	North Western Perimeter	LOGGED BY:	FJB	DATE:	6 April 2002
TERREIN:		BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 37' 55,4" S		
KLIENT:		POSISIE:	27° 48' 32,6" E		



SOIL KRAFT	SOIL PROFILE : AUGER HOLE 10	FIG B10
-----------------------	-------------------------------------	----------------

PROJECT:	Master Plan for Pollution Control - Iscor	AUGER HOLE:	11	SHEET No:	1
PROJEK:	Vanderbiil Park	AWEGAAR:		Vel Nr:	
SITE:		LOGGED BY:	FJB	DATE:	4 April 2002
TERREIN:	Southeastern Perimeter	BESKRYF:		DATUM:	
CLIENT:	Van Renssen & Fortuin	LOCATION:	26° 39' 00,0" S		
KLIENT:		POSISIE:	27° 50' 51,9" E		

Legend Lepende	Depth Diepte m	SOIL PROFILE - GRONDPROFIEL	Sample Monster
	0,30	Very moist, dark grey brown, very loose, intact, silty SAND . Fine colluvium.	
	0,90	Very moist, dark grey brown, medium dense, intact, silty SAND and matrix supported, rounded, medium coarse, gravels of ferricrete. Ferruginized fine colluvium.	
	2,00	Abundant clast supported, rounded, fine, black GRAVELS of ferricrete and angular to rounded CDBBLES of quartz, quartzite and chert in a matrix of very moist, dark brown, silty sand. Overall consistency is dense. Reworked quaternary gravels.	
	2,70	Abundant clast supported rounded COBBLES of quartz, quartzite and chert in a matrix of slightly moist, dark red brown, ferruginized cemented, silty sand. Overall consistency is very dense. Ferruginized quaternary gravels.	

	Water encountered Water teenekom	Contractor: Kontrakteur:	Frankipile	NOTES / NOTAS 1 Refusal of drilling encountered at 2700mm on very dense ferruginized quaternary gravels. 2 Seepage encountered between surface and 2000mm.
	Water level Waterpeilvlak	Date Drilled: Datum Geboor:	14 March 2002	
	Bottom of hole Bodem van gat	Machine: Masjien:	Williams Digger 11	
	Approximate material change Benaderende materiaalverandering	Hole diameter: Gat deursnee:	750mm	
	Disturbed sample Versteurde monster	Water depth: Waternvlak:		
	Undisturbed sample Onversteurde monster			
	Consolidation sample Konsolidasie monster			
	Indicator tests Waterspeelvlak			

SOIL KRAFT	SOIL PROFILE : AUGER HOLE 11	FIG B11
-----------------------	-------------------------------------	----------------

**ISCOR FLAT STEEL PRODUCTS VANDERBIJL
PARK : PROPOSED MASTER PLAN FOR WASTE
MANAGEMENT - FINAL GEOTECHNICAL REPORT**

9 ADDENDUM C

RESULTS OF DHS PROBING

PENETROMETER RESULTS

ROELF FOURIE

GEOTECHNICAL SERVICES

Cell. 082 440 2151

Job No.	RFQ1093/03/02	Remarks :
Project	REHABILITATION OF SILT DAMS	
Site	ISCOR V.D.BIJL	
Date	4,5,6,11,12,13-03-2002	
Done by	HANNES	

DEPTH	DPSH 1	DPSH 2	DPSH 3	DPSH 4	DPSH 5	DPSH 6	DPSH 7	DPSH 8	DPSH 9
0.3	10	44	13	29	16	19	75	49	25
0.6	19	43	20	63	14	14	80	42	80 REF.
0.9	80 REF.	39	38	24	24	12	70	30	
1.2		38	76	80 REF.	25	12	80 REF.	25	
1.5		36	58		19	34		29	
1.8		41	46		13	45		9	
2.1		24	28		15	43		7	
2.4		62	80 REF.		67	29		16	
2.7		80 REF.			73	80 REF.		35	
3.0					28			72	
3.3					80 REF.			73	
3.6								80	
3.9								80	
4.2								39	
4.5								30	
4.8								20	
5.1								80 REF.	
5.4									
5.7									
6.0									
6.3									
6.6									
6.9									
7.2									
7.5									
7.8									
8.1									
8.4									
8.7									
9.0									
9.3									
9.6									
9.9									
10.2									
10.5									
10.8									
11.1									
11.4									
11.7									
12.0									
12.3									
12.6									
12.9									
13.2									
13.5									
13.8									
14.1									
14.4									
14.7									
15.0									
15.3									
Redrive									
-0.3									

Draft for discussion
CONFIDENTIAL

PENETROMETER RESULTS

ROELF FOURIE

GEOTECHNICAL SERVICES

Cell. 082 440 2151

Job No.	RFQ1093/03/02	Remarks :
Project	REHABILITATION OF SILT DAMS	
Site	ISCOR V.D.BIJL	
Date	4,5,6,11,12,13-03-2002	
Done by	HANNES	

DEPTH	DPSH 10	DPSH 11	DPSH 12	DPSH 13	DPSH 14	DPSH 15	DPSH 16	DPSH 17	DPSH 18
0.3	11	110	16	9	1	1	8	2	1
0.6	20	19	8	28	3	3	33	6	9
0.9	50	18	41	76	3	17	30	39	50
1.2	16	92	48	145	5	80 REF.	58	80 REF.	80 REF.
1.5	80 REF.	50	55	80 REF.	27		80 REF.		
1.8		10	28		80 REF.				
2.1		7	13						
2.4		16	20						
2.7		18	13						
3.0		20	14						
3.3		18	14						
3.6		18	15						
3.9		18	13						
4.2		18	12						
4.5		18	12						
4.8		18	12						
5.1		21	13						
5.4		23	15						
5.7		26	19						
6.0		29	17						
6.3		26	20						
6.6		30	23						
6.9		30	24						
7.2		39	29						
7.5		40	32						
7.8		45	33						
8.1		48	36						
8.4		51	36						
8.7		58	39						
9.0		63	41						
9.3		73	46						
9.6		76	53						
9.9		80 REF.	64						
10.2			76						
10.5			80 REF						
10.8									
11.1									
11.4									
11.7									
12.0									
12.3									
12.6									
12.9									
13.2									
13.5									
13.8									
14.1									
14.4									
14.7									
15.0									
Redrive									
0.3									
0.6									

Draft for discussion
CONFIDENTIAL
Research for IYS

PENETROMETER RESULTS

ROELF FOURIE

GEOTECHNICAL SERVICES

Cell. 082 440 2151

Job No.	RFQ1093/03/02	Remarks :
Project	REHABILITATION OF SILT DAMS	
Site	ISCOR V.D BIJL	
Date	4,5,6,11,12,13-03-2002	
Done by	HANNES	

DEPTH	DPSH 19	DPSH 20	DPSH 21	DPSH 22	DPSH 23	DPSH 24	DPSH 25	DPSH 26	DPSH 27
0.3	9	17	6	16	11	17	15	30	27
0.6	20	13	10	15	8	9	18	19	14
0.9	74	3	7	5	3	6	9	8	7
1.2	60	5	12	6	2	5	11	15	13
1.5	80 REF.	4	12	7	2	10	18	27	23
1.8		3	16	8	4	14	24	50	25
2.1		4	22	14	4	13	46	44	23
2.4		39	80 REF.	15	7	13	60	59	31
2.7		22		18	17	23	60	57	26
3.0		8		13	20	22	80 REF.	70	43
3.3		14		22	30	58		80 REF.	47
3.6		26		28	14	63			50
3.9		19		49	31	74			72
4.2		24		62	31	80 REF.			80 REF.
4.5		26		80 REF.	27				
4.8		30			26				
5.1		37			28				
5.4		46			31				
5.7		44			31				
6.0		64			37				
6.3		68			38				
6.6		74			56				
6.9		80 REF.			64				
7.2					75				
7.5					80 REF.				
7.8									
8.1									
8.4									
8.7									
9.0									
9.3									
9.6									
9.9									
10.2									
10.5									
10.8									
11.1									
11.4									
11.7									
12.0									
12.3									
12.6									
12.9									
13.2									
13.5									
13.8									
14.1									
14.4									
14.7									
15.0									
Redrive									
0.3									
0.6									

Draft for discussion
CONFIDENTIAL
Research for IVS

ENETROMETER RESULTS

ROELF FOURIE

GEOTECHNICAL SERVICES

Cell. 082 440 2151

Job No. Project Site Date Done by	RFQ1093/03/02			Remarks :					
	REHABILITATION OF SILT DAMS								
	ISCOR V.D BIJL								
	4,5,6,11,12,13-03-2002								
	HANNES								
DEPTH	DPSH 28	DPSH 29	DPSH 30	DPSH 31	DPSH 32	DPSH 33	DPSH 34	DPSH 35	DPSH 36
0.3	15	30	9	24	24	18	25	16	52
0.6	25	15	4	14	49	14	12	19	24
0.9	40	9	4	8	7	8	4	7	14
1.2	70	14	8	9	16	8	5	7	15
1.5	80 REF.	29	30	46	48	25	11	7	19
1.8		78	60	56	61	20	18	18	48
2.1		80 REF.	44	77	42	24	26	25	53
2.4			61	80 REF.	80 REF.	17	28	44	60
2.7			80 REF.			16	31	57	80 REF.
3.0						19	38	80 REF.	
3.3						17	30		
3.6						21	28		
3.9						80 REF.	36		
4.2							59		
4.5							80 REF.		
4.8									
5.1									
5.4									
5.7									
6.0									
6.3									
6.6									
6.9									
7.2									
7.5									
7.8									
8.1									
8.4									
8.7									
9.0									
9.3									
9.6									
9.9									
10.2									
10.5									
10.8									
11.1									
11.4									
11.7									
12.0									
12.3									
12.6									
12.9									
13.2									
13.5									
13.8									
14.1									
14.4									
14.7									
15.0									
Redrive									
0.3									
0.6									

Draft for discussion
CONFIDENTIAL
Research for RVS

Draft for Discussion
CONFIDENTIAL
Research for IYS

PENETROMETER RESULTS

KOELF FOURIE

GEOTECHNICAL SERVICES

Cell. 082 440 21

Job No.	RFQ1093/03/02	Remarks :
Project	REHABILITATION OF SILT DAMS	
Site	ISCOR V.D. BIJL	
Date	4,5,6,11,12,13-03-2002	
Done by	HANNES	

DEPTH	DPSH 37	DPSH 38	DPSH 39	DPSH 40	DPSH 41	DPSH 42	DPSH 43	DPSH 44	DPSH 45
0.3	14	9	13	1	10	26	33	166	100
0.6	15	6	6	2	5	13	8	REF.	120
0.9	5	19	7	2	5	80 REF.	14		REF.
1.2	8	37	6	4	7		15		
1.5	20	80 REF.	5	7	8		12		
1.8	20		5	12	15		12		
2.1	44		24	25	18		9		
2.4	38		38	72	18		13		
2.7	43		46	80 REF.	14		18		
3.0	62		44		14		20		
3.3	49		52		28		35		
3.6	48		57		26		80 REF.		
3.9	80 REF.		51		80 REF.				
4.2			58						
4.5			44						
4.8			25						
5.1			26						
5.4			28						
5.7			23						
6.0			25						
6.3			25						
6.6			80 REF.						
6.9									
7.2									
7.5									
7.8									
8.1									
8.4									
8.7									
9.0									
9.3									
9.6									
9.9									
10.2									
10.5									
10.8									
11.1									
11.4									
11.7									
12.0									
12.3									
12.6									
12.9									
13.2									
13.5									
13.8									
14.1									
Redrive									
0.3									
0.6									

PENETROMETER RESULTS

ROELF FOURIE

GEOTECHNICAL SERVICES

Cell. 082 440 21

Job No. RFQ1093/03/02
Project REHABILITATION OF SILT DAMS
Site ISCOR V.D. BIJL
Date 4,5,6,11,12,13-03-2002
Done by HANNES

Remarks :

DEPTH	DPSH 46	DPSH 47	DPSH 48	DPSH 49	DPSH 50	DPSH 51	DPSH 52	DPSH 53	DPSH 54
0.3	11	100	120	160	180	63	69	88	44
0.6	6	41	105	110	REF.	25	30	34	22
0.9	4	7	68	52		16	13	45	32
1.2	16	4	80 REF.	40		25	18	16	27
1.5	9	12		28		54	33	16	14
1.8	5	33		80 REF.		20	28	48	15
2.1	7	45				14	44	80 REF.	10
2.4	12	80 REF.				50	80 REF.		80 REF.
2.7	28					42			
3.0	33					31			
3.3	31					80 REF.			
3.6	25								
3.9	20								
4.2	19								
4.5	19								
4.8	19								
5.1	24								
5.4	20								
5.7	28								
6.0	30								
6.3	27								
6.6	39								
6.9	40								
7.2	40								
7.5	42								
7.8	42								
8.1	40								
8.4	43								
8.7	40								
9.0	41								
9.3	43								
9.6	49								
9.9	40								
10.2	47								
10.5	80 REF.								
10.8									
11.1									
11.4									
11.7									
12.0									
12.3									
12.6									
12.9									
13.2									
13.5									
13.8									
14.1									
14.4									
14.7									
15.0									
15.3									
Redrive									
0.3									
0.6									

PENETROMETER RESULTS

ROELF FOURIE


GEOTECHNICAL SERVICES

Cell. 082 440 21

Job No. RFQ1093/03/02
Project REHABILITATION OF SILT DAMS
Site ISCOR V.D.BIJL
Date 4,5,6,11,12,13-03-2002
Done by HANNES

Remarks :


DEPTH	DPSH 55	DPSH 56							
0.3	69	48							
0.6	31	29							
0.9	14	33							
1.2	25	63							
1.5	51	59							
1.8	80 REF.	64							
2.1		80 REF.							
2.4									
2.7									
3.0									
3.3									
3.6									
3.9									
4.2									
4.5									
4.8									
5.1									
5.4									
5.7									
6.0									
6.3									
6.6									
6.9									
7.2									
7.5									
7.8									
8.1									
8.4									
8.7									
9.0									
9.3									
9.6									
9.9									
10.2									
10.5									
10.8									
11.1									
11.4									
11.7									
12.0									
12.3									
12.6									
12.9									
13.2									
13.5									
13.8									
Redrive									
0.3									
0.6									



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 1


**FIGURE
C1**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 2


**FIGURE
C2**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 3


**FIGURE
C3**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 4


**FIGURE
C4**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 5


**FIGURE
C5**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 6


**FIGURE
C6**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 7


**FIGURE
C7**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 8


**FIGURE
C8**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 9


**FIGURE
C9**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 10

**FIGURE
C10**




**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 11

**FIGURE
C11**


Draft for discussion
CONFIDENTIAL
Research for IVS



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 12


**FIGURE
C12**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 13


**FIGURE
C13**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 14


**FIGURE
C14**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 15


**FIGURE
C15**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 16


**FIGURE
C16**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 17


**FIGURE
C17**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 18

**FIGURE
C18**




**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 19

**FIGURE
C19**


Draft for discussion
CONFIDENTIAL
Research for IVS



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 20


**FIGURE
C20**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 21


**FIGURE
C21**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 22


**FIGURE
C22**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 23


**FIGURE
C23**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 24


**FIGURE
C24**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 25


**FIGURE
C25**



SOIL
KRAFT

PENETRATION CURVE : DHSPT 26


FIGURE
C26



SOIL
KRAFT

PENETRATION CURVE : DHSPT 27


FIGURE
C27



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 28


**FIGURE
C28**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 29


**FIGURE
C29**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 30


**FIGURE
C30**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 31


**FIGURE
C31**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 32


**FIGURE
C32**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 33


**FIGURE
C33**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 34


**FIGURE
C34**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 35


**FIGURE
C35**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 36


**FIGURE
C36**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 37


**FIGURE
C37**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 38


**FIGURE
C38**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 39


**FIGURE
C39**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 40


**FIGURE
C40**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 41


**FIGURE
C41**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 42


**FIGURE
C42**



SOIL
KRAFT

PENETRATION CURVE : DHSPT 43


FIGURE
C43



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 44


**FIGURE
C44**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 45


**FIGURE
C45**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 46


**FIGURE
C46**



SOIL
KRAFT

PENETRATION CURVE : DHSPT 47


FIGURE
C47



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 48


**FIGURE
C48**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 49


**FIGURE
C49**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 50


**FIGURE
C50**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 51


**FIGURE
C51**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 52


**FIGURE
C52**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 53


**FIGURE
C53**



**SOIL
KRAFT**

PENETRATION CURVE : DH5PT 55

**FIGURE
C55**



**SOIL
KRAFT**

PENETRATION CURVE : DHSPT 56

**FIGURE
C56**

**ISCOR FLAT STEEL PRODUCTS VANDERBIJL
PARK : PROPOSED MASTER PLAN FOR WASTE
MANAGEMENT - FINAL GEOTECHNICAL REPORT**

10 ADDENDUM D


RESULTS OF SOIL TESTING

PARTICLE SIZE ANALYSIS



Sample / Hole No.	4594	4595
Depth (m)	1.4 - 2.2	0.9 - 1.9
Position	TP 2	TP 4
Material Description	DARK BROWN FERRICRETE SILTY SAND	LIGHT GREY CALCRETE SANDY GRAVEL
Moisture (%)		
SCREEN ANALYSIS (% PASSING)		
63.0 mm	100	100
53.0 mm	100	100
37.5 mm	100	100
26.6 mm	100	100
19.0 mm	100	100
13.2 mm	98	96
4.75 mm	84	72
2.00 mm	71	38
0.425 mm	60	19
0.075 mm	46	14
HYDROMETER ANALYSIS		
0.040 mm	24	9
0.027 mm	20	8
0.013 mm	16	7
0.005 mm	11	6
0.002 mm	6	4
% Clay	6	4
% Silt	31	8
% Sand	34	26
% Gravel	29	62
ATTERBERG LIMITS		
Liquid Limit	42	81
Plasticity Index	20	42
Linear Shrinkage	10.0	18.0
Grading Modulus	1.23	2.29
Classification	A-7.6(5)	A-2.7(0)
Unified Classification	SC	SC
Chart Reference	■—■—■	▲—▲—▲

PROJECT : ISCOR FLAT STEEL PRODUCTS - NEW DAM
JOB NR. : S02-193
DATE : 2002-03-01

POTENTIAL EXPANSIVENESS



PLASTICITY CHART



HIDROMETER/193-02

SOILLAB

(PTY) LTD

Reg No 71/00112/07

230 Albertus Street
La Montagne
Tel (012) 481-3999

CONFIDENTIAL
Research for


P.O. Box 72928
Lynnwood Ridge 0040
Fax (012) 481-3812

PARTICLE SIZE ANALYSIS



Sample / Hole No.	04596	
Depth (m)	1.1 - 2.5	
Position	TP 6	
Material Description	DARK YELLOW FERRICRETE SANDY GRAVEL	
Moisture (%)		
SCREEN ANALYSIS (% PASSING)		
63.0 mm	100	
53.0 mm	100	
37.5 mm	100	
28.5 mm	100	
19.0 mm	100	
13.2 mm	100	
4.75 mm	76	
2.00 mm	69	
0.425 mm	64	
0.075 mm	47	
HYDROMETER ANALYSIS		
0.040 mm	33	
0.027 mm	31	
0.013 mm	28	
0.005 mm	23	
0.002 mm	18	
% Clay	18	
% Silt	23	
% Sand	28	
% Gravel	31	
ATTERBERG LIMITS		
Liquid Limit	51	
Plasticity Index	25	
Linear Shrinkage	11.0	
Grading Modulus	1.20	
Classification	A 7-6(8)	
Unified Classification	SC	
Chart Reference	—*—*—	—▲—▲—

PROJECT : ISCOR FLAT STEEL PRODUCTS - NEW DAM
JOB NR. : S02-193
DATE : 2002-03-01

POTENTIAL EXPANSIVENESS



PLASTICITY CHART



HIDROMETER/193-03

Draft for discussion

SOILLAB

(PTY) LTD
Reg No 71/00112/07

230 Albertus Street
La Montagne
Tel (012) 481-3999

CONFIDENTIAL
Research


P.O. Box 72928
Lynnwood Ridge 0040
Fax (012) 481-8812

PARTICLE SIZE ANALYSIS



Sample / Hole No.	4592	4593
Depth (m)	0.4-2.0	0.2-1.2
Position	TP 9	TP 11
Material Description	DARK BROWN FERRICRETE CLAYEY SAND	DARK BROWN FERRICRETE CLAYEY SAND
Moisture (%)		
SCREEN ANALYSIS (% PASSING)		
63.0 mm	100	100
53.0 mm	100	100
37.5 mm	100	100
26.5 mm	100	100
19.0 mm	100	100
13.2 mm	98	100
4.75 mm	91	97
2.00 mm	86	94
0.425 mm	82	85
0.075 mm	58	59
HYDROMETER ANALYSIS		
0.040 mm	43	42
0.027 mm	38	37
0.013 mm	36	36
0.005 mm	34	32
0.002 mm	33	29
% Clay	33	29
% Silt	19	23
% Sand	35	42
% Gravel	14	6
ATTERBERG LIMITS		
Liquid Limit	45	45
Plasticity Index	23	23
Linear Shrinkage	10.5	10.5
Grading Modulus	0.74	0.62
Classification	A-7-6(10)	A-7-6(11)
Unified Classification	CL	CL
Chart Reference	■-■-■	▲-▲-▲

PROJECT : ISCOR FLAT STEEL PRODUCTS - NEW DAM
JOB NR. : S02-193
DATE : 2002-03-01

POTENTIAL EXPANSIVENESS



PLASTICITY CHART



Draft for discussion
CONFIDENTIAL
Research

SOILLAB

(PTY) LTD
Reg No 71/00112/07

230 Albertus Street
La Montagne
Tel (012) 481-3999

Box 72928
Lynnwood Ridge 0040
Fax (012) 481-3912/3

PARTICLE SIZE ANALYSIS


Sample / Hole No.	4597	4598
Depth (m)	1.9 - 2.8	1.9 - 2.7
Position	TP 2	TP 4
Material Description	DARK YELLOW FERRICRETE SANDY SILT	DARK YELLOW FERRICRETE SANDY SILT
Moisture (%)		
SCREEN ANALYSIS (% PASSING)		
63.0 mm	100	100
53.0 mm	100	100
37.5 mm	100	100
26.5 mm	100	100
19.0 mm	100	100
13.2 mm	100	100
4.75 mm	93	99
2.00 mm	86	93
0.425 mm	78	87
0.075 mm	66	72
HYDROMETER ANALYSIS		
0.040 mm	31	47
0.027 mm	27	42
0.013 mm	22	35
0.005 mm	16	26
0.002 mm	11	21
% Clay	11	21
% Silt	40	40
% Sand	35	32
% Gravel	14	7
ATTERBERG LIMITS		
Liquid Limit	46	47
Plasticity Index	21	22
Linear Shrinkage	10.0	10.0
Grading Modulus	0.70	0.48
Classification	A-7-6(11)	A-7-6(14)
Unified Classification	CL	CL
Chart Reference	■-■-■	▲-▲-▲

PROJECT : ISCOR FLAT STEEL PRODUCTS - WASTE SITE



JOB NR. : S02.193

DATE : 2002-03-01

POTENTIAL EXPANSIVENESS



PLASTICITY CHART



HYDROMETER/193-04

SOILLAB

(PTY) LTD

Page No 71/00112/07

230 Albertus Street
La Montagne
Tel (012) 481-3999

Draft for Discussion
P.O. Box 72928
Lynnwood Ridge 0040
Fax (012) 481-3912
Research for IVS

PARTICLE SIZE ANALYSIS


Sample / Hole No.	4599	
Depth (m)	1.9 - 2.8	
Position	TP 7	
Material Description	DARK BROWN SHALE	
	SANDY GRAVEL	
Moisture (%)		
SCREEN ANALYSIS (% PASSING)		
63.0 mm	100	
53.0 mm	100	
37.5 mm	100	
26.5 mm	100	
19.0 mm	100	
13.2 mm	99	
4.75 mm	81	
2.00 mm	64	
0.425 mm	50	
0.075 mm	40	
HYDROMETER ANALYSIS		
0.040 mm	28	
0.027 mm	26	
0.013 mm	22	
0.005 mm	15	
0.002 mm	12	
% Clay	12	
% Silt	23	
% Sand	29	
% Gravel	36	
ATTERBERG LIMITS		
Liquid Limit	33	
Plasticity Index	13	
Linear Shrinkage	6.5	
Grading Modulus	1.46	
Classification	A-6(2)	
Unified Classification	SC	
Chart Reference	■—■—■	▲—▲—▲

PROJECT : ISCOR FLAT STEEL PRODUCTS - WASTE SITE



JOB NR. : S02-193

DATE : 2002-03-01

POTENTIAL EXPANSIVENESS



PLASTICITY CHART



HYDROMETER/193-05

Draft for discussion

CONFIDENTIAL

Res 2012/1813912

SOILLAB

(PTY) LTD
Reg No 71/00112/07



230 Albertus Street
La Montagne
Tel (012) 481-3999

DIRECT SHEAR TEST

PROJECT

ISCOR

SAMPLE NO.	SAMPLE DEPTH (m)	NORMAL STRESS (kN/m ²)	PEAK SHEAR		PEAK ANGLE OF INTERNAL FRICTION (DEG)	COHESION (kN/m ²)	OPTIMUM MOISTURE (%)	MOISTURE AFTER TEST (%)	PROCTOR DRY DENSITY (kg/m ³)
			STRESS (kN/m ²)	DISPLACEMENT (mm)					
TP ND 4	0.9-1.9	50	11.2	1.50	38.8	0.0	21.4	32.5	1540
		100	66.6	5.14					
		200	134.9	7.52					



NOTE(1): THE ABOVE REMOULDED SOIL SAMPLE WERE TESTED IN A SATURATED CONDITION UNDER SELECTED NORMAL LOADS IN A 50 mm DIAMETER BOX USING A CONTROLLED RATE OF DISPLACEMENT OF 0.1307 mm PER MINUTE.

NOTE(2): THE ABOVE SAMPLES WERE COMPACTED TO 95 % OF PROCTOR DRY DENSITY @ OPTIMUM MOISTURE CONDITION.

BOXSHR/193-01

SOILLAB

(PTY) LTD

Reg No 71/00112/07

230 Albertus Street
La Montagne
Tel (012) 481-3999



Draft for discussion
CONFIDENTIAL
Research & Dev

DIRECT SHEAR TEST

PROJECT

ISCOR

SAMPLE NO.	SAMPLE DEPTH (m)	NORMAL STRESS (kN/m ²)	PEAK SHEAR		PEAK ANGLE OF INTERNAL FRICTION (DEG)	COHESION (kN/m ²)	OPTIMUM MOISTURE (%)	MOISTURE AFTER TEST (%)	PROCTOR DRY DENSITY (kg/m ³)
			STRESS (kN/m ²)	DISPLACEMENT (mm)					
TP ND 9	0.4-2.0	50	12.3	3.47	30.7	0.0	18.1	25.9	1638
		100	66.6	5.39					
		200	106.4	4.33					



NOTE(1): THE ABOVE REMOULDED SOIL SAMPLE WERE TESTED IN A SATURATED CONDITION UNDER SELECTED NORMAL LOADS IN A 50 mm DIAMETER BOX USING A CONTROLLED RATE OF DISPLACEMENT OF 0.1473 mm PER MINUTE.

NOTE(2): THE ABOVE SAMPLES WERE COMPACTED TO 95 % OF PROCTOR DRY DENSITY @ OPTIMUM MOISTURE CONDITION.

BOXSHR/193-02

Draft for discussion

SOILLAB

(PTY) LTD

Reg No 71/00112/07

230 Albertus Street
La Montagne
Tel (012) 481-3999


P O Box 72928
Dunwood Ridge 0040
Fax (012) 481-3812

PARTICLE SIZE ANALYSIS



Sample / Hole No.	4600	4601
Depth (m)	0.7 - 0.8	1.0-2.5
Position	TP 6	TP 10
Material Description	DARK BROWN FERRICRETE SANDY GRAVEL	DARK R/O FERRICRETE CLAYEY SILT
Moisture (%)		
SCREEN ANALYSIS (% PASSING)		
63.0 mm	100	100
53.0 mm	100	100
37.5 mm	100	100
26.5 mm	100	100
19.0 mm	100	100
13.2 mm	95	98
4.75 mm	51	92
2.00 mm	24	90
0.425 mm	20	85
0.075 mm	11	70
HYDROMETER ANALYSIS		
0.040 mm	7	49
0.027 mm	5	46
0.013 mm	4	43
0.005 mm	3	34
0.002 mm	2	29
% Clay	2	29
% Silt	7	32
% Sand	15	29
% Gravel	76	10
ATTERBERG LIMITS		
Liquid Limit	22	51
Plasticity Index	8	25
Linear Shrinkage	4.0	10.5
Grading Modulus	2.45	0.55
Classification	A-2-4(0)	A-7-6(15)
Unified Classification	SP & SC	CH
Chart Reference	■—■—■	▲—▲—▲

PROJECT: ISCOR FLAT STEEL PRODUCTS - EXSISTING DAMS
JOB NR. : S02-193
DATE : 2002-03-01

POTENTIAL EXPANSIVENESS



PLASTICITY CHART



HYDROMETER/193-06

SOILLAB

(PTY) LTD
Reg No 71/00112/07

230 Albertus Street
La Montagne
Tel (012) 481-3999

CONFIDENTIAL
P.O. Box 72928
Lynnwood Ridge 0040
Fax (012) 481-3812

CLIENT : SOILKRAFT
 PROJECT : ISCOR
 PROJECT NO. : S02-193
 DATE : 2002-04-08

PERMEABILITY ON REMOULDED SAMPLES

Sample (no)	Depth (m)	Max. Proctor dry density (kg/m ³)	Optimum moisture content (%)	Compaction as percent of Max. Proctor dry density (%)	Head of water (cm)	Coefficient of permeability (cm/s)
TP ND2	1.4-2.2	1642	19.8	95.0	51.0	5.033×10^{-6}
TP NW2	1.9-2.8	1614	20.4	95.0	51.0	1.117×10^{-5}
TP NW7	1.9-2.8	1789	13.9	90.0	51.0	6.669×10^{-4}
TP ED10	1.0-2.5	1528	21.9	90.0	51.0	3.668×10^{-5}
TP ND11	0.2-1.2	1593	17.3	95.0	51.0	1.083×10^{-5}

193-01

- 1 -


Draft for discussion
CONFIDENTIAL
 Research for IVS

PARTICLE SIZE ANALYSIS



Sample / Hole No.	4602	4603
Depth (m)	0.85 - 2.9	1.5-2.85
Position	TP 1	TP 3
Material Description	DARK OLIVE FERRICRETE SILTY SAND	DARK YELLOW FERRICRETE GRAVELLY SAND
Moisture (%)		
SCREEN ANALYSIS (% PASSING)		
63.0 mm	100	100
53.0 mm	100	100
37.5 mm	100	100
26.5 mm	100	100
19.0 mm	100	100
13.2 mm	100	100
4.75 mm	96	82
2.00 mm	92	76
0.425 mm	88	71
0.075 mm	66	50
HYDROMETER ANALYSIS		
0.040 mm	46	34
0.027 mm	42	31
0.013 mm	40	28
0.005 mm	35	26
0.002 mm	28	23
% Clay	28	23
% Silt	29	20
% Sand	35	33
% Gravel	8	24
ATTERBERG LIMITS		
Liquid Limit	59	39
Plasticity Index	30	20
Linear Shrinkage	13.5	9.0
Grading Modulus	0.54	1.03
Classification	A-7.6(17)	A-6(7)
Unified Classification	CH	CL
Chart Reference	■—■—■	▲—▲—▲

PROJECT : ISCOR FLAT STEEL PRODUCTS - CLAY LINER
JOB NR. : S02-193
DATE : 2002-03-01

POTENTIAL EXPANSIVENESS



PLASTICITY CHART



HYDROMETER/193-07

SOILLAB

(PTY) LTD

Reg No 71/00112/07

230 Albertus Street
La Montagne
Tel (012) 481-3999


CONFIDENTIAL
Research for ISCOR
P.O. Box 72928
Lynnwood Ridge 0040
Fax (012) 481-38125

PARTICLE SIZE ANALYSIS



Sample / Hole No.	4604	4605
Depth (m)	0-1.1	0.95-2.9
Position	TP 5	TP 8
Material Description	DARK GREY FERRICRETE CLAYEY SAND	DARK BROWN FERRICRETE SANDY GRAVEL
Moisture (%)		
SCREEN ANALYSIS (% PASSING)		
63.0 mm	100	100
53.0 mm	100	100
37.5 mm	100	100
25.0 mm	100	100
19.0 mm	100	100
13.2 mm	100	100
4.75 mm	99	82
2.00 mm	94	58
0.425 mm	74	43
0.075 mm	47	32
HYDROMETER ANALYSIS		
0.040 mm	34	20
0.027 mm	31	17
0.013 mm	30	15
0.005 mm	25	12
0.002 mm	22	10
% Clay	22	10
% Silt	19	16
% Sand	53	31
% Gravel	6	42
ATTERBERG LIMITS		
Liquid Limit	45	49
Plasticity Index	23	23
Linear Shrinkage	10.5	10.0
Grading Modulus	0.85	1.67
Classification	A-7-6(7)	A-2-7(2)
Unified Classification	SC	SC
Chart Reference	■-■-■	▲-▲-▲

PROJECT : ISCOR FLAT-STEEL PRODUCTS - CLAY LINER
JOB NR. : S02-193
DATE : 2002-03-01

POTENTIAL EXPANSIVENESS



PLASTICITY CHART



HYDROMETER/193-08

SOILLAB

(PTY) LTD
Reg No 71/00112/07

230 Albertus Street
La Montagne
Tel (012) 481-3999


Draft for discussion
CONFIDENTIAL
Research for IVS
P.O. Box 72928
Lynnwood Ridge 0040
Fax (012) 481-3812

PARTICLE SIZE ANALYSIS



Sample / Hole No.	4608
Depth (m)	1.0-2.81
Position	TP 17
Material Description	DARK Y/O CLAYEY SAND
Moisture (%)	
SCREEN ANALYSIS (% PASSING)	
63.0 mm	100
53.0 mm	100
37.5 mm	100
26.5 mm	100
19.0 mm	100
13.2 mm	100
4.75 mm	99
2.00 mm	98
0.425 mm	93
0.075 mm	62
HYDROMETER ANALYSIS	
0.040 mm	45
0.027 mm	39
0.013 mm	37
0.005 mm	37
0.002 mm	32
% Clay	32
% Silt	23
% Sand	43
% Gravel	2
ATTERBERG LIMITS	
Liquid Limit	45
Plasticity Index	23
Linear Shrinkage	10.5
Grading Modulus	0.47
Classification	A-7-6(11)
Unified Classification	CL
Chart Reference	■ ■ ■ ■ ▲ ▲ ▲ ▲

PROJECT : ISCOR FLAT STEEL PRODUCTS - CLAY LINER
JOB NR. : S02-193
DATE : 2002-03-01

POTENTIAL EXPANSIVENESS



PLASTICITY CHART



Draft for discussion

SOILLAB

(PTY) LTD
Reg No 71/00112/07

230 Albertus Street
La Montagne
Tel (012) 481-3999

P.O. Box 72928
Lynwood Ridge 0040
Fax (012) 481-3812